

FLORA LUX

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5060100903000516	460 x 520	5	29	245	56-82	72-98	43-69	4	100	0,58	C-E-D
5060100903000724	460 x 720	7	29	245	56-82	72-98	43-69	4	100	0,81	C-E-D
5060100903000932	460 x 930	9	29	245	56-82	72-98	43-69	4	100	1,03	C-E-D
5060100903001140	460 x 1140	11	29	245	56-82	72-98	43-69	4	100	1,26	C-E-D
5060100903001348	460 x 1350	13	29	245	56-82	72-98	43-69	4	100	1,48	C-E-D
5060100903001556	460 x 1560	15	29	245	56-82	72-98	43-69	4	100	1,71	C
5060100903001764	460 x 1760	17	29	245	56-82	72-98	43-69	4	100	1,93	C
5060100903001972	460 x 1970	19	29	245	56-82	72-98	43-69	4	100	2,15	C
5060100904000516	560 x 520	5	29	345	56-82	72-98	43-69	4	100	0,65	C-E-D
5060100904000724	560 x 720	7	29	345	56-82	72-98	43-69	4	100	0,91	C-E-D
5060100904000932	560 x 930	9	29	345	56-82	72-98	43-69	4	100	1,16	C-E-D
5060100904001140	560 x 1140	11	29	345	56-82	72-98	43-69	4	100	1,42	C-E-D
5060100904001348	560 x 1350	13	29	345	56-82	72-98	43-69	4	100	1,67	C-E-D
5060100904001556	560 x 1560	15	29	345	56-82	72-98	43-69	4	100	1,92	C
5060100904001764	560 x 1760	17	29	345	56-82	72-98	43-69	4	100	2,17	C
5060100904001972	560 x 1970	19	29	345	56-82	72-98	43-69	4	100	2,42	C
5060100905000516	660 x 520	5	29	445	56-82	72-98	43-69	4	100	0,73	C-E-D
5060100905000724	660 x 720	7	29	445	56-82	72-98	43-69	4	100	1,01	C-E-D
5060100905000932	660 x 930	9	29	445	56-82	72-98	43-69	4	100	1,29	C-E-D
5060100905001140	660 x 1140	11	29	445	56-82	72-98	43-69	4	100	1,57	C-E-D
5060100905001348	660 x 1350	13	29	445	56-82	72-98	43-69	4	100	1,85	C-E-D
5060100905001556	660 x 1560	15	29	445	56-82	72-98	43-69	4	100	2,13	C
5060100905001764	660 x 1760	17	29	445	56-82	72-98	43-69	4	100	2,41	C
5060100905001972	660 x 1970	19	29	445	56-82	72-98	43-69	4	100	2,69	C
5060100906000516	760 x 520	5	29	545	56-82	72-98	43-69	4	100	0,80	C-E-D
5060100906000724	760 x 720	7	29	545	56-82	72-98	43-69	4	100	1,11	C-E-D
5060100906000932	760 x 930	9	29	545	56-82	72-98	43-69	4	100	1,41	C-E-D
5060100906001140	760 x 1140	11	29	545	56-82	72-98	43-69	4	100	1,73	C-E-D
5060100906001348	760 x 1350	13	29	545	56-82	72-98	43-69	4	100	2,04	C-E-D
5060100906001556	760 x 1560	15	29	545	56-82	72-98	43-69	4	100	2,35	C
5060100906001764	760 x 1760	17	29	545	56-82	72-98	43-69	4	100	2,66	C
5060100906001972	760 x 1970	19	29	545	56-82	72-98	43-69	4	100	2,96	C
5060100907000516	860 x 520	5	29	645	56-82	72-98	43-69	4	100	0,87	C-E-D
5060100907000724	860 x 720	7	29	645	56-82	72-98	43-69	4	100	1,21	C-E-D
5060100907000932	860 x 930	9	29	645	56-82	72-98	43-69	4	100	1,54	C-E-D
5060100907001140	860 x 1140	11	29	645	56-82	72-98	43-69	4	100	1,89	C-E-D
5060100907001348	860 x 1350	13	29	645	56-82	72-98	43-69	4	100	2,23	C-E-D
5060100907001556	860 x 1560	15	29	645	56-82	72-98	43-69	4	100	2,56	C
5060100907001764	860 x 1760	17	29	645	56-82	72-98	43-69	4	100	2,90	C
5060100907001972	860 x 1970	19	29	645	56-82	72-98	43-69	4	100	3,24	C
5060100908000516	960 x 520	5	29	745	56-82	72-98	43-69	4	100	0,94	C-E-D
5060100908000724	960 x 720	7	29	745	56-82	72-98	43-69	4	100	1,31	C-E-D
5060100908000932	960 x 930	9	29	745	56-82	72-98	43-69	4	100	1,67	C-E-D
5060100908001140	960 x 1140	11	29	745	56-82	72-98	43-69	4	100	2,05	C-E-D
5060100908001348	960 x 1350	13	29	745	56-82	72-98	43-69	4	100	2,41	C-E-D
5060100908001556	960 x 1560	15	29	745	56-82	72-98	43-69	4	100	2,78	C
5060100908001764	960 x 1760	17	29	745	56-82	72-98	43-69	4	100	3,14	C
5060100908001972	960 x 1970	19	29	745	56-82	72-98	43-69	4	100	3,51	C
5060100909000516	1060 x 520	5	29	845	56-82	72-98	43-69	4	100	1,01	C-E-D
5060100909000724	1060 x 720	7	29	845	56-82	72-98	43-69	4	100	1,41	C-E-D
5060100909000932	1060 x 930	9	29	845	56-82	72-98	43-69	4	100	1,80	C-E-D
5060100909001140	1060 x 1140	11	29	845	56-82	72-98	43-69	4	100	2,20	C-E-D
5060100909001348	1060 x 1350	13	29	845	56-82	72-98	43-69	4	100	2,60	C-E-D
5060100909001556	1060 x 1560	15	29	845	56-82	72-98	43-69	4	100	2,99	C
5060100909001764	1060 x 1760	17	29	845	56-82	72-98	43-69	4	100	3,39	C
5060100909001972	1060 x 1970	19	29	845	56-82	72-98	43-69	4	100	3,78	C
5060100910000516	1160 x 520	5	29	945	56-82	72-98	43-69	4	100	1,08	C-E-D
5060100910000724	1160 x 720	7	29	945	56-82	72-98	43-69	4	100	1,51	C-E-D
5060100910000932	1160 x 930	9	29	945	56-82	72-98	43-69	4	100	1,93	C-E-D
5060100910001140	1160 x 1140	11	29	945	56-82	72-98	43-69	4	100	2,36	C-E-D
5060100910001348	1160 x 1350	13	29	945	56-82	72-98	43-69	4	100	2,78	C-E-D
5060100910001556	1160 x 1560	15	29	945	56-82	72-98	43-69	4	100	3,21	C
5060100910001764	1160 x 1760	17	29	945	56-82	72-98	43-69	4	100	3,63	C
5060100910001972	1160 x 1970	19	29	945	56-82	72-98	43-69	4	100	4,05	C
5060100912000516	1360 x 520	5	29	1145	56-82	72-98	43-69	4	100	1,23	C-E-D
5060100912000724	1360 x 720	7	29	1145	56-82	72-98	43-69	4	100	1,71	C-E-D
5060100912000932	1360 x 930	9	29	1145	56-82	72-98	43-69	4	100	2,19	C-E-D
5060100912001140	1360 x 1140	11	29	1145	56-82	72-98	43-69	4	100	2,68	C-E-D
5060100912001348	1360 x 1350	13	29	1145	56-82	72-98	43-69	4	100	3,16	C-E-D
5060100912001556	1360 x 1560	15	29	1145	56-82	72-98	43-69	4	100	3,64	C
5060100914000516	1560 x 520	5	29	1345	56-82	72-98	43-69	4	100	1,37	C-E-D
5060100914000724	1560 x 720	7	29	1345	56-82	72-98	43-69	4	100	1,91	C-E-D
5060100914000932	1560 x 930	9	29	1345	56-82	72-98	43-69	4	100	2,44	C-E-D
5060100914001140	1560 x 1140	11	29	1345	56-82	72-98	43-69	4	100	2,99	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5060100903000516	137	466	178	606
5060100903000724	191	653	249	849
5060100903000932	246	839	320	1091
5060100903001140	301	1026	391	1334
5060100903001348	356	1213	462	1576
5060100903001556	410	1399	533	1819
5060100903001764	465	1586	605	2061
5060100903001972	520	1772	676	2304
5060100904000516	186	636	242	826
5060100904000724	261	890	339	1157
5060100904000932	335	1144	436	1487
5060100904001140	410	1398	533	1818
5060100904001348	485	1652	630	2148
5060100904001556	559	1907	727	2479
5060100904001764	634	2161	824	2809
5060100904001972	708	2415	921	3140
5060100905000516	238	812	310	1056
5060100905000724	333	1137	433	1478
5060100905000932	429	1462	557	1900
5060100905001140	524	1786	681	2322
5060100905001348	619	2111	805	2744
5060100905001556	714	2436	929	3167
5060100905001764	810	2761	1052	3589
5060100905001972	905	3086	1176	4011
5060100906000516	292	996	380	1295
5060100906000724	409	1394	532	1813
5060100906000932	526	1793	683	2330
5060100906001140	643	2191	835	2848
5060100906001348	759	2589	987	3366
5060100906001556	876	2988	1139	3884
5060100906001764	993	3386	1291	4402
5060100906001972	1110	3784	1443	4920
5060100907000516	333	1137	433	1478
5060100907000724	467	1591	607	2069
5060100907000932	600	2046	780	2660
5060100907001140	733	2501	953	3261
5060100907001348	867	2956	1127	3842
5060100907001556	1000	3410	1300	4433
5060100907001764	1133	3865	1473	5025
5060100907001972	1267	4320	1647	5616
5060100908000516	373	1271	485	1652
5060100908000724	522	1780	678	2313
5060100908000932	671	2288	872	2974
5060100908001140	820	2796	1066	3635
5060100908001348	969	3305	1260	4296
5060100908001556	1118	3813	1454	4957
5060100908001764	1267	4322	1648	5618
5060100908001972	1416	4830	1841	6279
5060100909000516	410	1399	533	1819
5060100909000724	574	1959	747	2546
5060100909000932	739	2518	960	3274
5060100909001140	903	3078	1173	4001
5060100909001348	1067	3638	1387	4729
5060100909001556	1231	4197	1600	5456
5060100909001764	1395	4757	1813	6184
5060100909001972	1559	5317	2027	6912
5060100910000516	446	1521	580	1977
5060100910000724	624	2129	812	2768
5060100910000932	803	2738	1044	3559
5060100910001140	981	3346	1276	4350
5060100910001348	1160	3955	1508	5141
5060100910001556	1338	4563	1740	5932
5060100910001764	1517	5171	1971	6723
5060100910001972	1695	5780	2203	7514
5060100912000516	512	1746	666	2270
5060100912000724	717	2445	932	3178
5060100912000932	922	3143	1198	4086
5060100912001140	1127	3842	1465	4994
5060100912001348	1332	4540	1731	5903
5060100912001556	1536	5239	1997	6811
5060100914000516	588	2005	764	2607
5060100914000724	823	2807	1070	3649
5060100914000932	1058	3609	1376	4692
5060100914001140	1294	4411	1682	5734

FLORA LUX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
				√	x	x	x	√	√		

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
mm	Watt	Btu	Watt	Btu

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm