

OTIS DOUBLE LUX

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5060102103000308	380 x 310	3	68	245	63-72	95-104	26-35	4	100	0,33	C
5060102103000412	380 x 410	4	68	245	63-72	95-104	26-35	4	100	0,42	C-E-D
5060102103000516	380 x 520	5	68	245	63-72	95-104	26-35	4	100	0,52	C-E-D
5060102103000620	380 x 620	6	68	245	63-72	95-104	26-35	4	100	0,62	C-E-D
5060102103000724	380 x 720	7	68	245	63-72	95-104	26-35	4	100	0,72	C-E-D
5060102103000828	380 x 830	8	68	245	63-72	95-104	26-35	4	100	0,82	C-E-D
5060102103000932	380 x 930	9	68	245	63-72	95-104	26-35	4	100	0,92	C-E-D
5060102103001036	380 x 1040	10	68	245	63-72	95-104	26-35	4	100	1,03	C-E-D
5060102103001140	380 x 1140	11	68	245	63-72	95-104	26-35	4	100	1,13	C-E-D
5060102103001244	380 x 1240	12	68	245	63-72	95-104	26-35	4	100	1,22	C-E-D
5060102103001348	380 x 1350	13	68	245	63-72	95-104	26-35	4	100	1,32	C-E-D
5060102103001452	380 x 1450	14	68	245	63-72	95-104	26-35	4	100	1,42	C
5060102103001556	380 x 1560	15	68	245	63-72	95-104	26-35	4	100	1,52	C
5060102103001660	380 x 1660	16	68	245	63-72	95-104	26-35	4	100	1,62	C
5060102103001764	380 x 1760	17	68	245	63-72	95-104	26-35	4	100	1,71	C
5060102103001868	380 x 1870	18	68	245	63-72	95-104	26-35	4	100	1,81	C
5060102103001972	380 x 1970	19	68	245	63-72	95-104	26-35	4	100	1,91	C
5060102104000308	480 x 310	3	68	345	63-72	95-104	26-35	4	100	0,37	C
5060102104000412	480 x 410	4	68	345	63-72	95-104	26-35	4	100	0,48	C-E-D
5060102104000516	480 x 520	5	68	345	63-72	95-104	26-35	4	100	0,59	C-E-D
5060102104000620	480 x 620	6	68	345	63-72	95-104	26-35	4	100	0,71	C-E-D
5060102104000724	480 x 720	7	68	345	63-72	95-104	26-35	4	100	0,82	C-E-D
5060102104000828	480 x 830	8	68	345	63-72	95-104	26-35	4	100	0,93	C-E-D
5060102104000932	480 x 930	9	68	345	63-72	95-104	26-35	4	100	1,04	C-E-D
5060102104001036	480 x 1040	10	68	345	63-72	95-104	26-35	4	100	1,17	C-E-D
5060102104001140	480 x 1140	11	68	345	63-72	95-104	26-35	4	100	1,28	C-E-D
5060102104001244	480 x 1240	12	68	345	63-72	95-104	26-35	4	100	1,40	C-E-D
5060102104001348	480 x 1350	13	68	345	63-72	95-104	26-35	4	100	1,51	C-E-D
5060102104001452	480 x 1450	14	68	345	63-72	95-104	26-35	4	100	1,62	C
5060102104001556	480 x 1560	15	68	345	63-72	95-104	26-35	4	100	1,73	C
5060102104001660	480 x 1660	16	68	345	63-72	95-104	26-35	4	100	1,85	C
5060102104001764	480 x 1760	17	68	345	63-72	95-104	26-35	4	100	1,96	C
5060102104001868	480 x 1870	18	68	345	63-72	95-104	26-35	4	100	2,07	C
5060102104001972	480 x 1970	19	68	345	63-72	95-104	26-35	4	100	2,18	C
5060102105000308	580 x 310	3	68	445	63-72	95-104	26-35	4	100	0,41	C
5060102105000412	580 x 410	4	68	445	63-72	95-104	26-35	4	100	0,54	C-E-D
5060102105000516	580 x 520	5	68	445	63-72	95-104	26-35	4	100	0,67	C-E-D
5060102105000620	580 x 620	6	68	445	63-72	95-104	26-35	4	100	0,79	C-E-D
5060102105000724	580 x 720	7	68	445	63-72	95-104	26-35	4	100	0,92	C-E-D
5060102105000828	580 x 830	8	68	445	63-72	95-104	26-35	4	100	1,05	C-E-D
5060102105000932	580 x 930	9	68	445	63-72	95-104	26-35	4	100	1,17	C-E-D
5060102105001036	580 x 1040	10	68	445	63-72	95-104	26-35	4	100	1,31	C-E-D
5060102105001140	580 x 1140	11	68	445	63-72	95-104	26-35	4	100	1,44	C-E-D
5060102105001244	580 x 1240	12	68	445	63-72	95-104	26-35	4	100	1,57	C-E-D
5060102105001348	580 x 1350	13	68	445	63-72	95-104	26-35	4	100	1,69	C-E-D
5060102105001452	580 x 1450	14	68	445	63-72	95-104	26-35	4	100	1,82	C
5060102105001556	580 x 1560	15	68	445	63-72	95-104	26-35	4	100	1,95	C
5060102105001660	580 x 1660	16	68	445	63-72	95-104	26-35	4	100	2,07	C
5060102105001764	580 x 1760	17	68	445	63-72	95-104	26-35	4	100	2,20	C
5060102105001868	580 x 1870	18	68	445	63-72	95-104	26-35	4	100	2,33	C
5060102105001972	580 x 1970	19	68	445	63-72	95-104	26-35	4	100	2,45	C
5060102106000308	680 x 310	3	68	545	63-72	95-104	26-35	4	100	0,45	C
5060102106000412	680 x 410	4	68	545	63-72	95-104	26-35	4	100	0,60	C-E-D
5060102106000516	680 x 520	5	68	545	63-72	95-104	26-35	4	100	0,74	C-E-D
5060102106000620	680 x 620	6	68	545	63-72	95-104	26-35	4	100	0,88	C-E-D
5060102106000724	680 x 720	7	68	545	63-72	95-104	26-35	4	100	1,02	C-E-D
5060102106000828	680 x 830	8	68	545	63-72	95-104	26-35	4	100	1,16	C-E-D
5060102106000932	680 x 930	9	68	545	63-72	95-104	26-35	4	100	1,30	C-E-D
5060102106001036	680 x 1040	10	68	545	63-72	95-104	26-35	4	100	1,46	C-E-D
5060102106001140	680 x 1140	11	68	545	63-72	95-104	26-35	4	100	1,60	C-E-D
5060102106001244	680 x 1240	12	68	545	63-72	95-104	26-35	4	100	1,74	C-E-D
5060102106001348	680 x 1350	13	68	545	63-72	95-104	26-35	4	100	1,88	C-E-D
5060102106001452	680 x 1450	14	68	545	63-72	95-104	26-35	4	100	2,02	C
5060102106001556	680 x 1560	15	68	545	63-72	95-104	26-35	4	100	2,16	C
5060102106001660	680 x 1660	16	68	545	63-72	95-104	26-35	4	100	2,30	C
5060102106001764	680 x 1760	17	68	545	63-72	95-104	26-35	4	100	2,44	C
5060102106001868	680 x 1870	18	68	545	63-72	95-104	26-35	4	100	2,59	C
5060102106001972	680 x 1970	19	68	545	63-72	95-104	26-35	4	100	2,73	C
5060102107000308	780 x 310	3	68	645	63-72	95-104	26-35	4	100	0,50	C
5060102107000412	780 x 410	4	68	645	63-72	95-104	26-35	4	100	0,65	C-E-D
5060102107000516	780 x 520	5	68	645	63-72	95-104	26-35	4	100	0,81	C-E-D
5060102107000620	780 x 620	6	68	645	63-72	95-104	26-35	4	100	0,96	C-E-D
5060102107000724	780 x 720	7	68	645	63-72	95-104	26-35	4	100	1,12	C-E-D
5060102107000828	780 x 830	8	68	645	63-72	95-104	26-35	4	100	1,27	C-E-D
5060102107000932	780 x 930	9	68	645	63-72	95-104	26-35	4	100	1,43	C-E-D
5060102107001036	780 x 1040	10	68	645	63-72	95-104	26-35	4	100	1,60	C-E-D
5060102107001140	780 x 1140	11	68	645	63-72	95-104	26-35	4	100	1,75	C-E-D
5060102107001244	780 x 1240	12	68	645	63-72	95-104	26-35	4	100	1,91	C-E-D
5060102107001348	780 x 1350	13	68	645	63-72	95-104	26-35	4	100	2,07	C-E-D
5060102107001452	780 x 1450	14	68	645	63-72	95-104	26-35	4	100	2,22	C
5060102107001556	780 x 1560	15	68	645	63-72	95-104	26-35	4	100	2,38	C

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		
	mm	Watt	Btu	Watt	Btu
5060102103000308	151	514	196	668	
5060102103000412	201	685	261	890	
5060102103000516	251	856	326	1113	
5060102103000620	301	1028	392	1336	
5060102103000724	352	1199	457	1558	
5060102103000828	402	1370	522	1781	
5060102103000932	452	1541	588	2004	
5060102103001036	502	1712	653	2226	
5060102103001140	552	1884	718	2449	
5060102103001244	603	2055	783	2671	
5060102103001348	653	2226	849	2894	
5060102103001452	703	2397	914	3117	
5060102103001556	753	2569	979	3339	
5060102103001660	804	2740	1045	3562	
5060102103001764	854	2911	1110	3785	
5060102103001868	904	3082	1175	4007	
5060102103001972	954	3254	1240	4230	
5060102104000308	205	700	267	910	
5060102104000412	274	933	356	1214	
5060102104000516	342	1167	445	1517	
5060102104000620	411	1400	534	1820	
5060102104000724	479	1634	623	2124	
5060102104000828	547	1867	712	2427	
5060102104000932	616	2100	801	2730	
5060102104001036	684	2334	890	3034	
5060102104001140	753	2567	979	3337	
5060102104001244	821	2800	1068	3641	
5060102104001348	890	3034	1157	3944	
5060102104001452	958	3267	1246	4247	
5060102104001556	1027	3501	1335	4551	
5060102104001660	1095	3734	1423	4854	
5060102104001764	1163	3967	1512	5157	
5060102104001868	1232	4201	1601	5461	
5060102104001972	1300	4434	1690	5764	
5060102105000308	262	894	341	1163	
5060102105000412	350	1193	455	1550	
5060102105000516	437	1491	568	1938	
5060102105000620	525	1789	682	2326	
5060102105000724	612	2087	796	2713	
5060102105000828	699	2385	909	3101	
5060102105000932	787	2683	1023	3488	
5060102105001036	874	2982	1137	3876	
5060102105001140	962	3280	1250	4264	
5060102105001244	1049	3578	1364	4651	
5060102105001348	1137	3876	1478	5039	
5060102105001452	1224	4174	1591	5426	
5060102105001556	1312	4472	1705	5814	
5060102105001660	1399	4770	1819	6202	
5060102105001764	1486	5069	1932	6589	
5060102105001868	1574	5367	2046	6977	
5060102105001972	1661	5665	2160	7364	
5060102106000308	322	1097	418	1426	
5060102106000412	429	1463	558	1902	
5060102106000516	536	1828	697	2377	
5060102106000620	643	2194	836	2852	
5060102106000724	751	2560	976	3328	
5060102106000828	858	2925	1115	3803	
5060102106000932	965	3291	1255	4278	
5060102106001036	1072	3657	1394	4754	
5060102106001140	1180	4022	1533	5229	
5060102106001244	1287	4388	1673	5705	
5060102106001348	1394	4754	1812	6180	
5060102106001452	1501	5120	1952	6655	
5060102106001556	1609	5485	2091	7131	
5060102106001660	1716	5851	2231	7606	
5060102106001764	1823	6217	2370	8082	
5060102106001868	1930	6582	2509	8557	
5060102106001972	2038	6948	2649	9032	
5060102107000308	367	1252	477	1628	
5060102107000412	490	1670	637	2171	
5060102107000516	612	2087	796	2713	
5060102107000620	734	2504	955	3256	
5060102107000724	857	2922	1114	3798	
5060102107000828	979	3339	1273	4341	
5060102107000932	1102	3757	1432	4884	
5060102107001036	1224	4174	1591	5426	
5060102107001140	1346	4592	1750	5969	
5060102107001244	1469	5009	1910	6512	
5060102107001348	1591	5426	2069	7054	
5060102107001452	1714	5844	2228	7597	
5060102107001556	1836	6261	2387	8140	

OTIS DOUBLE LUX

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5060102107001660	780 x 1660	16	68	645	63-72	95-104	26-35	4	100	2,53	C
5060102107001764	780 x 1760	17	68	645	63-72	95-104	26-35	4	100	2,69	C
5060102107001868	780 x 1870	18	68	645	63-72	95-104	26-35	4	100	2,84	C
5060102107001972	780 x 1970	19	68	645	63-72	95-104	26-35	4	100	3,00	C
5060102108000308	880 x 310	3	68	745	63-72	95-104	26-35	4	100	0,54	C
5060102108000412	880 x 410	4	68	745	63-72	95-104	26-35	4	100	0,71	C-E-D
5060102108000516	880 x 520	5	68	745	63-72	95-104	26-35	4	100	0,88	C-E-D
5060102108000620	880 x 620	6	68	745	63-72	95-104	26-35	4	100	1,05	C-E-D
5060102108000724	880 x 720	7	68	745	63-72	95-104	26-35	4	100	1,22	C-E-D
5060102108000828	880 x 830	8	68	745	63-72	95-104	26-35	4	100	1,39	C-E-D
5060102108000932	880 x 930	9	68	745	63-72	95-104	26-35	4	100	1,56	C-E-D
5060102108001036	880 x 1040	10	68	745	63-72	95-104	26-35	4	100	1,74	C-E-D
5060102108001140	880 x 1140	11	68	745	63-72	95-104	26-35	4	100	1,91	C-E-D
5060102108001244	880 x 1240	12	68	745	63-72	95-104	26-35	4	100	2,08	C-E-D
5060102108001348	880 x 1350	13	68	745	63-72	95-104	26-35	4	100	2,25	C-E-D
5060102108001452	880 x 1450	14	68	745	63-72	95-104	26-35	4	100	2,42	C
5060102108001556	880 x 1560	15	68	745	63-72	95-104	26-35	4	100	2,59	C
5060102108001660	880 x 1660	16	68	745	63-72	95-104	26-35	4	100	2,76	C
5060102108001764	880 x 1760	17	68	745	63-72	95-104	26-35	4	100	2,93	C
5060102108001868	880 x 1870	18	68	745	63-72	95-104	26-35	4	100	3,10	C
5060102108001972	880 x 1970	19	68	745	63-72	95-104	26-35	4	100	3,27	C
5060102109000308	980 x 310	3	68	845	63-72	95-104	26-35	4	100	0,58	C
5060102109000412	980 x 410	4	68	845	63-72	95-104	26-35	4	100	0,77	C-E-D
5060102109000516	980 x 520	5	68	845	63-72	95-104	26-35	4	100	0,95	C-E-D
5060102109000620	980 x 620	6	68	845	63-72	95-104	26-35	4	100	1,14	C-E-D
5060102109000724	980 x 720	7	68	845	63-72	95-104	26-35	4	100	1,32	C-E-D
5060102109000828	980 x 830	8	68	845	63-72	95-104	26-35	4	100	1,50	C-E-D
5060102109000932	980 x 930	9	68	845	63-72	95-104	26-35	4	100	1,69	C-E-D
5060102109001036	980 x 1040	10	68	845	63-72	95-104	26-35	4	100	1,89	C-E-D
5060102109001140	980 x 1140	11	68	845	63-72	95-104	26-35	4	100	2,07	C-E-D
5060102109001244	980 x 1240	12	68	845	63-72	95-104	26-35	4	100	2,25	C-E-D
5060102109001348	980 x 1350	13	68	845	63-72	95-104	26-35	4	100	2,44	C-E-D
5060102109001452	980 x 1450	14	68	845	63-72	95-104	26-35	4	100	2,62	C
5060102109001556	980 x 1560	15	68	845	63-72	95-104	26-35	4	100	2,81	C
5060102109001660	980 x 1660	16	68	845	63-72	95-104	26-35	4	100	2,99	C
5060102109001764	980 x 1760	17	68	845	63-72	95-104	26-35	4	100	3,17	C
5060102109001868	980 x 1870	18	68	845	63-72	95-104	26-35	4	100	3,36	C
5060102109001972	980 x 1970	19	68	845	63-72	95-104	26-35	4	100	3,54	C
5060102110000308	1080 x 310	3	68	945	63-72	95-104	26-35	4	100	0,63	C
5060102110000412	1080 x 410	4	68	945	63-72	95-104	26-35	4	100	0,82	C-E-D
5060102110000516	1080 x 520	5	68	945	63-72	95-104	26-35	4	100	1,02	C-E-D
5060102110000620	1080 x 620	6	68	945	63-72	95-104	26-35	4	100	1,22	C-E-D
5060102110000724	1080 x 720	7	68	945	63-72	95-104	26-35	4	100	1,42	C-E-D
5060102110000828	1080 x 830	8	68	945	63-72	95-104	26-35	4	100	1,62	C-E-D
5060102110000932	1080 x 930	9	68	945	63-72	95-104	26-35	4	100	1,82	C-E-D
5060102110001036	1080 x 1040	10	68	945	63-72	95-104	26-35	4	100	2,03	C-E-D
5060102110001140	1080 x 1140	11	68	945	63-72	95-104	26-35	4	100	2,23	C-E-D
5060102110001244	1080 x 1240	12	68	945	63-72	95-104	26-35	4	100	2,43	C-E-D
5060102110001348	1080 x 1350	13	68	945	63-72	95-104	26-35	4	100	2,62	C-E-D
5060102110001452	1080 x 1450	14	68	945	63-72	95-104	26-35	4	100	2,82	C
5060102110001556	1080 x 1560	15	68	945	63-72	95-104	26-35	4	100	3,02	C
5060102110001660	1080 x 1660	16	68	945	63-72	95-104	26-35	4	100	3,22	C
5060102110001764	1080 x 1760	17	68	945	63-72	95-104	26-35	4	100	3,42	C
5060102110001868	1080 x 1870	18	68	945	63-72	95-104	26-35	4	100	3,61	C
5060102110001972	1080 x 1970	19	68	945	63-72	95-104	26-35	4	100	3,81	C
5060102112000308	1280 x 310	3	68	1145	63-72	95-104	26-35	4	100	0,71	C
5060102112000412	1280 x 410	4	68	1145	63-72	95-104	26-35	4	100	0,94	C-E-D
5060102112000516	1280 x 520	5	68	1145	63-72	95-104	26-35	4	100	1,17	C-E-D
5060102112000620	1280 x 620	6	68	1145	63-72	95-104	26-35	4	100	1,39	C-E-D
5060102112000724	1280 x 720	7	68	1145	63-72	95-104	26-35	4	100	1,62	C-E-D
5060102112000828	1280 x 830	8	68	1145	63-72	95-104	26-35	4	100	1,85	C-E-D
5060102112000932	1280 x 930	9	68	1145	63-72	95-104	26-35	4	100	2,07	C-E-D
5060102112001036	1280 x 1040	10	68	1145	63-72	95-104	26-35	4	100	2,31	C-E-D
5060102112001140	1280 x 1140	11	68	1145	63-72	95-104	26-35	4	100	2,54	C-E-D
5060102112001244	1280 x 1240	12	68	1145	63-72	95-104	26-35	4	100	2,77	C-E-D
5060102112001348	1280 x 1350	13	68	1145	63-72	95-104	26-35	4	100	3,00	C-E-D
5060102114000308	1480 x 310	3	68	1345	63-72	95-104	26-35	4	100	0,80	C
5060102114000412	1480 x 410	4	68	1345	63-72	95-104	26-35	4	100	1,05	C-E-D
5060102114000516	1480 x 520	5	68	1345	63-72	95-104	26-35	4	100	1,31	C-E-D
5060102114000620	1480 x 620	6	68	1345	63-72	95-104	26-35	4	100	1,56	C-E-D
5060102114000724	1480 x 720	7	68	1345	63-72	95-104	26-35	4	100	1,82	C-E-D
5060102114000828	1480 x 830	8	68	1345	63-72	95-104	26-35	4	100	2,08	C-E-D
5060102114000932	1480 x 930	9	68	1345	63-72	95-104	26-35	4	100	2,33	C-E-D
5060102114001036	1480 x 1040	10	68	1345	63-72	95-104	26-35	4	100	2,60	C-E-D
5060102114001140	1480 x 1140	11	68	1345	63-72	95-104	26-35	4	100	2,86	C-E-D
5060102114001244	1480 x 1240	12	68	1345	63-72	95-104	26-35	4	100	3,11	C-E-D
5060102114001348	1480 x 1350	13	68	1345	63-72	95-104	26-35	4	100	3,37	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5060102107001660	1959	6679	2546	8682
5060102107001764	2081	7096	2705	9225
5060102107001868	2203	7513	2864	9767
5060102107001972	2326	7931	3023	10310
5060102108000308	411	1400	534	1820
5060102108000412	547	1867	712	2427
5060102108000516	684	2334	890	3034
5060102108000620	821	2800	1068	3641
5060102108000724	958	3267	1246	4247
5060102108000828	1095	3734	1423	4854
5060102108000932	1232	4201	1601	5461
5060102108001036	1369	4667	1779	6068
5060102108001140	1506	5134	1957	6674
5060102108001244	1642	5601	2135	7281
5060102108001348	1779	6068	2313	7888
5060102108001452	1916	6534	2491	8495
5060102108001556	2053	7001	2669	9101
5060102108001660	2190	7468	2847	9708
5060102108001764	2327	7935	3025	10315
5060102108001868	2464	8401	3203	10922
5060102108001972	2601	8868	3381	11528
5060102109000308	452	1541	588	2004
5060102109000412	603	2055	783	2671
5060102109000516	753	2569	979	3339
5060102109000620	904	3082	1175	4007
5060102109000724	1055	3596	1371	4675
5060102109000828	1205	4110	1567	5343
5060102109000932	1356	4624	1763	6011
5060102109001036	1507	5137	1959	6679
5060102109001140	1657	5651	2154	7346
5060102109001244	1808	6165	2350	8014
5060102109001348	1959	6679	2546	8682
5060102109001452	2109	7192	2742	9350
5060102109001556	2260	7706	2938	10018
5060102109001660	2410	8220	3134	10686
5060102109001764	2561	8734	3329	11354
5060102109001868	2712	9247	3525	12021
5060102109001972	2862	9761	3721	12689
5060102110000308	491	1675	639	2178
5060102110000412	655	2234	852	2904
5060102110000516	819	2792	1065	3630
5060102110000620	983	3351	1277	4356
5060102110000724	1146	3909	1490	5082
5060102110000828	1310	4468	1703	5808
5060102110000932	1474	5026	1916	6534
5060102110001036	1638	5585	2129	7260
5060102110001140	1802	6143	2342	7986
5060102110001244	1965	6702	2555	8712
5060102110001348	2129	7260	2768	9438
5060102110001452	2293	7819	2981	10165
5060102110001556	2457	8377	3194	10891
5060102110001660	2620	8936	3407	11617
5060102110001764	2784	9494	3620	12343
5060102110001868	2948	10053	3832	13069
5060102110001972	3112	10611	4045	13795
5060102112000308	564	1924	733	2501
5060102112000412	752	2565	978	3334
5060102112000516	940	3206	1222	4168
5060102112000620	1128	3847	1467	5002
5060102112000724	1316	4489	1711	5835
5060102112000828	1504	5130	1956	6669
5060102112000932	1692	5771	2200	7502
5060102112001036	1880	6412	2445	8336
5060102112001140	2069	7054	2689	9170
5060102112001244	2257	7695	2934	10003
5060102112001348	2445	8336	3178	10837
5060102114000308	648	2209	842	2871
5060102114000412	864	2945	1123	3828
5060102114000516	1080	3681	1403	4786
5060102114000620	1295	4417	1684	5743
5060102114000724	1511	5154	1965	6700
5060102114000828	1727	5890	2245	7657
5060102114000932	1943	6626	2526	8614
5060102114001036	2159	7362	2807	9571
5060102114001140	2375	8099	3087	10528
5060102114001244	2591	8835	3368	11485
5060102114001348	2807	9571	3649	12442

OTIS DOUBLE LUX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
				SX	ZX	YP	YL	AX	P3		
				✓	✓	✓	✓	✓	✓		

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
mm	Watt	Btu	Watt	Btu

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm

C: Central Heating / E: Electric / D: Dual Fuel