

BIANCO STAR

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5100100303651000	370 x 1000	4	120	945				4	80	1,01	C
5100100303651200	370 x 1200	4	120	1145				4	80	1,12	C
5100100303651400	370 x 1400	4	120	1345				4	80	1,24	C
5100100304500800	450 x 800	6	120	745				4	80	1,18	C
5100100304501000	450 x 1000	6	120	945				4	80	1,35	C
5100100304501200	450 x 1200	6	120	1145				4	80	1,52	C
5100100304501400	450 x 1400	6	120	1345				4	80	1,70	C
5100100305350800	540 x 800	8	120	745				4	80	1,47	C
5100100305351000	540 x 1000	8	120	945				4	80	1,69	C
5100100305351200	540 x 1200	8	120	1145				4	80	1,92	C
5100100305351400	540 x 1400	8	120	1345				4	80	2,15	C
5100100306200800	620 x 800	10	120	745				4	80	1,75	C
5100100306201000	620 x 1000	10	120	945				4	80	2,04	C
5100100306201200	620 x 1200	10	120	1145				4	80	2,32	C
5100100306201400	620 x 1400	10	120	1345				4	80	2,61	C

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5100100303651000	412	1404	535	1825
5100100303651200	473	1612	615	2096
5100100303651400	543	1851	706	2406
5100100304500800	516	1760	671	2288
5100100304501000	618	2106	803	2738
5100100304501200	709	2418	922	3144
5100100304501400	814	2776	1058	3609
5100100305350800	688	2347	895	3051
5100100305351000	824	2808	1071	3651
5100100305351200	946	3224	1229	4191
5100100305351400	1086	3702	1411	4812
5100100306200800	860	2934	1118	3814
5100100306201000	1029	3510	1338	4563
5100100306201200	1182	4030	1536	5239
5100100306201400	1357	4627	1764	6016

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
6,74	9,04	0,08	480X1025X152
7,62	10,17	0,09	480X1225X152
8,49	11,30	0,11	480X1425X152
7,98	10,21	0,08	570X825X152
9,30	11,80	0,09	570X1025X152
10,61	13,41	0,11	570X1225X152
11,93	15,02	0,13	570X1425X152
10,11	12,49	0,09	650X825X152
11,86	14,56	0,11	650X1025X152
13,62	16,63	0,13	650X1225X152
15,38	18,71	0,15	650X1425X152
12,24	14,79	0,10	740X825X152
14,43	17,33	0,12	740X1025X152
16,63	19,88	0,14	740X1225X152
18,82	22,43	0,17	740X1425X152

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	x	x	x	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel