

NISH STAR

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5100100806050800	610 x 800	4	120	745				4	200	1,12	C
5100100806051000	610 x 1000	4	120	945				4	200	1,24	C
5100100806051200	610 x 1200	4	120	1145				4	200	1,35	C
5100100806051400	610 x 1400	4	120	1345				4	200	1,47	C

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5100100806050800	562	1916	730	2491
5100100806051000	672	2293	874	2980
5100100806051200	772	2632	1003	3422
5100100806051400	886	3022	1152	3929

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
11,85	14,37	0,10	720X825X152
14,01	16,88	0,12	720X1025X152
16,17	19,38	0,14	720X1225X152
18,33	21,88	0,16	720X1425X152

C: Central Heating / E: Electric / D: Dual Fuel