

ORPIMENT STAR

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5100100904050800	410 x 800	4	120	745				4	100	0,93	C
5100100905100800	510 x 800	6	120	745				4	100	1,24	C
5100100906150800	620 x 800	8	120	745				4	100	1,54	C

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	x	x	x	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5100100904050800	1456	4966	1893	6456
5100100905100800	1872	6385	2434	8300
5100100906150800	2289	7804	2975	10145

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
6,90	9,03	0,07	520X825X152
9,53	11,87	0,08	630X825X152
12,18	14,72	0,10	730X825X152

C: Central Heating / E: Electric / D: Dual Fuel