

KALSEDON MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110100105750780	580 x 780	14	120	750				5	90	2,73	C
5110100105750970	580 x 970	18	120	940				5	90	3,16	C
5110100105751160	580 x 1160	22	120	1130				5	90	3,59	C
5110100105751350	580 x 1350	26	120	1320				5	90	4,02	C
5110100106750780	680 x 780	14	120	750				5	90	3,12	C
5110100106750970	680 x 970	18	120	940				5	90	3,61	C
5110100106751160	680 x 1160	22	120	1130				5	90	4,09	C
5110100106751350	680 x 1350	26	120	1320				5	90	4,58	C
5110100107750780	780 x 780	14	120	750				5	90	3,51	C
5110100107750970	780 x 970	18	120	940				5	90	4,05	C
5110100108750780	880 x 780	14	120	750				5	90	3,90	C
5110100108750970	880 x 970	18	120	940				5	90	4,50	C

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	mm	Watt	Btu	Btu
5110100105750780	1410	4807	1833	6249
5110100105750970	2169	7395	2819	9614
5110100105751160	3043	10378	3956	13491
5110100105751350	4130	14082	5368	18306
5110100106750780	1410	4807	1833	6249
5110100106750970	2169	7395	2819	9614
5110100106751160	3043	10378	3956	13491
5110100106751350	4130	14082	5368	18306
5110100107750780	1410	4807	1833	6249
5110100107750970	2169	7395	2819	9614
5110100108750780	1410	4807	1833	6249
5110100108750970	2169	7395	2819	9614

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
14,21	16,63	0,09	690X805X152
17,09	19,83	0,11	690X995X152
19,98	23,04	0,13	690X1185X152
22,86	26,23	0,15	690X1375X152
16,40	19,02	0,10	790X805X152
19,74	22,71	0,12	790X995X152
23,09	26,41	0,15	790X1185X152
26,43	30,10	0,17	790X1375X152
18,60	21,42	0,11	890X805X152
22,39	25,60	0,14	890X995X152
20,79	23,81	0,13	990X805X152
25,04	28,46	0,15	990X995X152

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel