

BELLA MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110100205750760	580 x 760	22	126	730				9	50	3,14	C
5110100205750880	580 x 880	26	126	850				9	50	3,49	C
5110100205751000	580 x 1000	30	126	970				9	50	3,84	C
5110100205751115	580 x 1120	34	126	1085				9	50	4,18	C
5110100205751235	580 x 1240	38	126	1205				9	50	4,53	C
5110100205751350	580 x 1350	42	126	1320				9	50	4,88	C
5110100206750760	680 x 760	22	126	730				9	50	3,64	C
5110100206750880	680 x 880	26	126	850				9	50	4,05	C
5110100206751000	680 x 1000	30	126	970				9	50	4,45	C
5110100206751115	680 x 1120	34	126	1085				9	50	4,86	C
5110100206751235	680 x 1240	38	126	1205				9	50	5,26	C
5110100206751350	680 x 1350	42	126	1320				9	50	5,67	C
5110100207750760	780 x 760	22	126	730				9	50	4,14	C
5110100207750880	780 x 880	26	126	850				9	50	4,61	C
5110100207751000	780 x 1000	30	126	970				9	50	5,07	C
5110100207751350	780 x 1350	42	126	1320				9	50	6,46	C
5110100208750760	880 x 760	22	126	730				9	50	4,65	C
5110100208750880	880 x 880	26	126	850				9	50	5,17	C
5110100208751000	880 x 1000	30	126	970				9	50	5,69	C
5110100208751350	880 x 1350	42	126	1320				9	50	7,25	C


HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5110100205750760	1738	5927	2260	7705
5110100205750880	2261	7710	2939	10023
5110100205751000	2836	9671	3687	12573
5110100205751115	3494	11916	4543	15490
5110100205751235	4125	14065	5362	18285
5110100205751350	5234	17849	6805	23204
5110100206750760	1738	5927	2260	7705
5110100206750880	2261	7710	2939	10023
5110100206751000	2836	9671	3687	12573
5110100206751115	3494	11916	4543	15490
5110100206751235	4125	14065	5362	18285
5110100206751350	5234	17849	6805	23204
5110100207750760	1738	5927	2260	7705
5110100207750880	2261	7710	2939	10023
5110100207751000	2836	9671	3687	12573
5110100207751350	5234	17849	6805	23204
5110100208750760	1738	5927	2260	7705
5110100208750880	2261	7710	2939	10023
5110100208751000	2836	9671	3687	12573
5110100208751350	5234	17849	6805	23204

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
14,50	16,90	0,09	690X785X158
16,40	19,00	0,10	690X905X158
18,30	21,11	0,12	690X1025X158
20,17	23,16	0,13	690X1140X158
22,08	25,29	0,14	690X1260X158
23,95	27,34	0,15	690X1375X158
16,75	19,36	0,10	790X785X158
18,95	21,77	0,12	790X905X158
21,15	24,20	0,13	790X1025X158
23,32	26,58	0,15	790X1140X158
25,53	29,00	0,16	790X1260X158
27,70	31,39	0,18	790X1375X158
19,00	21,78	0,12	890X785X158
21,50	24,53	0,13	890X905X158
24,00	27,28	0,15	890X1025X158
31,46	35,44	0,20	890X1375X158
21,24	24,22	0,13	990X785X158
24,04	27,29	0,15	990X905X158
26,85	30,37	0,17	990X1025X158
35,21	39,49	0,22	990X1375X158

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel