

ROYAL MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110100305750780	580 x 780	18	120	750				4	70	2,94	C
5110100305750930	580 x 930	22	120	900				4	70	3,33	C
5110100305751080	580 x 1080	26	120	1050				4	70	3,71	C
5110100305751213	580 x 1210	34	120	1183				4	70	4,29	C
5110100305751230	580 x 1230	30	120	1200				4	70	4,10	C
5110100306750780	680 x 780	18	120	750				4	70	3,39	C
5110100306750930	680 x 930	22	120	900				4	70	3,83	C
5110100306751080	680 x 1080	26	120	1050				4	70	4,27	C
5110100306751213	680 x 1210	34	120	1183				4	70	4,97	C
5110100306751230	680 x 1230	30	120	1200				4	70	4,71	C
5110100307750780	780 x 780	18	120	750				4	70	3,84	C
5110100307750930	780 x 930	22	120	900				4	70	4,34	C
5110100307751080	780 x 1080	26	120	1050				4	70	4,83	C
5110100308750780	880 x 780	18	120	750				4	70	4,28	C
5110100308750930	880 x 930	22	120	900				4	70	4,84	C
5110100308751080	880 x 1080	26	120	1050				4	70	5,40	C

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5110100305750780	1195	4074	1553	5296
5110100305750930	1607	5481	2089	7125
5110100305751080	2245	7655	2918	9951
5110100305751213	3100	10572	4030	13744
5110100305751230	2736	9328	3556	12127
5110100306750780	1195	4074	1553	5296
5110100306750930	1607	5481	2089	7125
5110100306751080	2245	7655	2918	9951
5110100306751213	3100	10572	4030	13744
5110100306751230	2736	9328	3556	12127
5110100307750780	1195	4074	1553	5296
5110100307750930	1607	5481	2089	7125
5110100307751080	2245	7655	2918	9951
5110100308750780	1195	4074	1553	5296
5110100308750930	1607	5481	2089	7125
5110100308751080	2245	7655	2918	9951

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
14,28	16,70	0,09	690X805X152
16,55	19,21	0,11	690X955X152
18,81	21,73	0,12	690X1105X152
23,32	26,73	0,13	690X1238X152
21,08	24,25	0,14	690X1255X152
16,46	19,08	0,10	790X805X152
19,09	21,99	0,12	790X955X152
21,72	24,89	0,14	790X1105X152
26,93	30,64	0,15	790X1238X152
24,34	27,79	0,16	790X1255X152
18,65	21,47	0,11	890X805X152
21,64	24,76	0,13	890X955X152
24,62	28,04	0,15	890X1105X152
20,84	23,86	0,13	990X805X152
24,18	27,53	0,15	990X955X152
27,52	31,19	0,17	990X1105X152

C: Central Heating / E: Electric / D: Dual Fuel