

AMAZONITE MAX

TECHNICAL INFORMATION

(For connection types, please refer to the last page)


MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110100405750635	580 x 640	10	137	605				4	100	2,35	C
5110100405750845	580 x 850	14	137	815				4	100	2,80	C
5110100405751050	580 x 1050	18	137	1020				4	100	3,25	C
5110100405751260	580 x 1260	22	137	1230				4	100	3,70	C
5110100406750635	680 x 640	10	137	605				4	100	2,68	C
5110100406750845	680 x 850	14	137	815				4	100	3,19	C
5110100406751050	680 x 1050	18	137	1020				4	100	3,70	C
5110100406751260	680 x 1260	22	137	1230				4	100	4,21	C
5110100407750635	780 x 640	10	137	605				4	100	3,02	C
5110100407750845	780 x 850	14	137	815				4	100	3,58	C
5110100407751050	780 x 1050	18	137	1020				4	100	4,14	C
5110100408750635	880 x 640	10	137	605				4	100	3,35	C
5110100408750845	880 x 850	14	137	815				4	100	3,97	C
5110100408751050	880 x 1050	18	137	1020				4	100	4,59	C

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
mm	Watf	Bfu	Watf	Bfu
5110100405750635	785	2675	1020	3478
5110100405750845	1402	4781	1823	6215
5110100405751050	2345	7996	3048	10395
5110100405751260	3291	11221	4278	14587
5110100406750635	785	2675	1020	3478
5110100406750845	1402	4781	1823	6215
5110100406751050	2345	7996	3048	10395
5110100406751260	3291	11221	4278	14587
5110100407750635	785	2675	1020	3478
5110100407750845	1402	4781	1823	6215
5110100407751050	2345	7996	3048	10395
5110100408750635	785	2675	1020	3478
5110100408750845	1402	4781	1823	6215
5110100408751050	2345	7996	3048	10395

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
12,22	14,45	0,08	690X660X169
15,47	18,05	0,11	690X870X169
18,68	21,61	0,13	690X1075X169
21,94	25,22	0,15	690X1285X169
14,13	16,52	0,09	790X660X169
17,90	20,68	0,12	790X870X169
21,65	24,83	0,15	790X1075X169
25,43	29,00	0,18	790X1285X169
16,03	18,59	0,10	890X660X169
20,33	23,33	0,14	890X870X169
24,61	28,02	0,17	890X1075X169
17,94	20,69	0,12	990X660X169
22,77	25,97	0,15	990X870X169
27,57	31,23	0,18	990X1075X169



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel