

BAMBOO MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110100505750720	580 x 720	10	120	690				1	119	2.45	C
5110100505750960	580 x 960	14	120	930				1	119	2.93	C
5110100505751200	580 x 1200	18	120	1170				1	119	3.42	C
5110100506750720	680 x 720	10	120	690				1	119	2.78	C
5110100506750960	680 x 960	14	120	930				1	119	3.32	C
5110100506751200	680 x 1200	18	120	1170				1	119	3.87	C
5110100507750720	780 x 720	10	120	690				1	119	3.11	C
5110100507750960	780 x 960	14	120	930				1	119	3.71	C
5110100508750720	880 x 720	10	120	690				1	119	3.44	C
5110100508750960	880 x 960	14	120	930				1	119	4.10	C

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5110100505750720	760	2593	988	3371
5110100505750960	1424	4857	1852	6314
5110100505751200	2102	7169	2733	9320
5110100506750720	760	2593	988	3371
5110100506750960	1424	4857	1852	6314
5110100506751200	2102	7169	2733	9320
5110100507750720	760	2593	988	3371
5110100507750960	1424	4857	1852	6314
5110100508750720	760	2593	988	3371
5110100508750960	1424	4857	1852	6314

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
12.66	14.99	0.08	690X745X152
16.06	18.79	0.11	690X985X152
19.45	22.57	0.13	690X1225X152
14.59	17.10	0.09	790X745X152
18.52	21.47	0.12	790X985X152
22.46	25.86	0.15	790X1225X152
16.52	19.22	0.11	890X745X152
20.99	24.16	0.14	890X985X152
18.45	21.33	0.12	990X745X152
23.46	26.86	0.15	990X985X152

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel