

OTIS MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110100605750635	580 x 640	10	120	605				4	100	2,35	C
5110100605750845	580 x 850	14	120	815				4	100	2,80	C
5110100605751050	580 x 1050	18	120	1020				4	100	3,25	C
5110100605751260	580 x 1260	22	120	1230				4	100	3,70	C
5110100606750635	680 x 640	10	120	605				4	100	2,68	C
5110100606750845	680 x 850	14	120	815				4	100	3,19	C
5110100606751050	680 x 1050	18	120	1020				4	100	3,70	C
5110100606751260	680 x 1260	22	120	1230				4	100	4,21	C
5110100607750635	780 x 640	10	120	605				4	100	3,02	C
5110100607750845	780 x 850	14	120	815				4	100	3,58	C
5110100607751050	780 x 1050	18	120	1020				4	100	4,14	C
5110100608750635	880 x 640	10	120	605				4	100	3,35	C
5110100608750845	880 x 850	14	120	815				4	100	3,97	C
5110100608751050	880 x 1050	18	120	1020				4	100	4,59	C

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5110100605750635	815	2779	1060	3613
5110100605750845	1456	4966	1893	6456
5110100605751050	2436	8306	3166	10797
5110100605751260	3418	11655	4443	15152
5110100606750635	815	2779	1060	3613
5110100606750845	1456	4966	1893	6456
5110100606751050	2436	8306	3166	10797
5110100606751260	3418	11655	4443	15152
5110100607750635	815	2779	1060	3613
5110100607750845	1456	4966	1893	6456
5110100607751050	2436	8306	3166	10797
5110100608750635	815	2779	1060	3613
5110100608750845	1456	4966	1893	6456
5110100608751050	2436	8306	3166	10797

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
11,31	13,50	0,07	690X660X152
14,19	16,73	0,10	690X870X152
17,04	19,92	0,12	690X1075X152
19,93	23,15	0,14	690X1285X152
12,96	15,31	0,08	790X660X152
16,27	19,01	0,11	790X870X152
19,55	22,68	0,13	790X1075X152
22,87	26,38	0,16	790X1285X152
14,62	17,14	0,09	890X660X152
18,36	21,31	0,12	890X870X152
22,07	25,43	0,15	890X1075X152
16,28	18,98	0,10	990X660X152
20,44	23,59	0,14	990X870X152
24,58	28,19	0,17	990X1075X152

C: Central Heating / E: Electric / D: Dual Fuel