

DIAMOND MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110101005750615	580 x 620	10	120	585				4	96	2,33	C
5110101005750815	580 x 820	14	120	785				4	96	2,77	C
5110101005751015	580 x 1020	18	120	985				4	96	3,21	C
5110101005751215	580 x 1220	22	120	1185				4	96	3,65	C
5110101006750615	680 x 620	10	120	585				4	96	2,66	C
5110101006750815	680 x 820	14	120	785				4	96	3,16	C
5110101006751015	680 x 1020	18	120	985				4	96	3,66	C
5110101006751215	680 x 1220	22	120	1185				4	96	4,15	C
5110101007750615	780 x 620	10	120	585				4	96	2,99	C
5110101007750815	780 x 820	14	120	785				4	96	3,55	C
5110101007751015	780 x 1020	18	120	985				4	96	4,10	C
5110101008750615	880 x 620	10	120	585				4	96	3,33	C
5110101008750815	880 x 820	14	120	785				4	96	3,94	C
5110101008751015	880 x 1020	18	120	985				4	96	4,55	C

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5110101005750615	820	2796	1066	3635
5110101005750815	1465	4997	1905	6496
5110101005751015	2254	7687	2931	9993
5110101005751215	3163	10787	4112	14023
5110101006750615	820	2796	1066	3635
5110101006750815	1465	4997	1905	6496
5110101006751015	2254	7687	2931	9993
5110101006751215	3163	10787	4112	14023
5110101007750615	820	2796	1066	3635
5110101007750815	1465	4997	1905	6496
5110101007751015	2254	7687	2931	9993
5110101008750615	820	2796	1066	3635
5110101008750815	1465	4997	1905	6496
5110101008751015	2254	7687	2931	9993

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
12,17	14,32	0,07	690X640X152
15,39	17,87	0,09	690X840X152
18,60	21,41	0,11	690X1040X152
21,83	24,97	0,14	690X1240X152
14,09	16,41	0,08	790X640X152
17,84	20,53	0,11	790X840X152
21,58	24,63	0,13	790X1040X152
25,34	28,76	0,15	790X1240X152
16,00	18,49	0,09	890X640X152
20,28	23,17	0,12	890X840X152
24,56	27,86	0,15	890X1040X152
17,92	20,56	0,10	990X640X152
22,73	25,82	0,13	990X840X152
27,54	31,06	0,16	990X1040X152

C: Central Heating / E: Electric / D: Dual Fuel