

FIONA MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110101105750620	580 x 620	10	130	590				1	99	2,33	C
5110101105750820	580 x 820	14	130	790				1	99	2,77	C
5110101105751020	580 x 1020	18	130	990				1	99	3,22	C
5110101105751220	580 x 1220	22	130	1190				1	99	3,66	C
5110101106750620	680 x 620	10	130	590				1	99	2,67	C
5110101106750820	680 x 820	14	130	790				1	99	3,16	C
5110101106751020	680 x 1020	18	130	990				1	99	3,66	C
5110101106751220	680 x 1220	22	130	1190				1	99	4,16	C
5110101107750620	780 x 620	10	130	590				1	99	3,00	C
5110101107750820	780 x 820	14	130	790				1	99	3,55	C
5110101107751020	780 x 1020	18	130	990				1	99	4,11	C
5110101108750620	880 x 620	10	130	590				1	99	3,33	C
5110101108750820	880 x 820	14	130	790				1	99	3,94	C
5110101108751020	880 x 1020	18	130	990				1	99	4,56	C

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5110101105750620	824	2809	1071	3652
5110101105750820	1472	5020	1914	6525
5110101105751020	2265	7722	2944	10039
5110101105751220	3178	10837	4131	14088
5110101106750620	824	2809	1071	3652
5110101106750820	1472	5020	1914	6525
5110101106751020	2265	7722	2944	10039
5110101106751220	3178	10837	4131	14088
5110101107750620	824	2809	1071	3652
5110101107750820	1472	5020	1914	6525
5110101107751020	2265	7722	2944	10039
5110101108750620	824	2809	1071	3652
5110101108750820	1472	5020	1914	6525
5110101108751020	2265	7722	2944	10039

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
12,28	14,46	0,08	690X645X162
15,53	18,04	0,10	690X845X162
18,78	21,63	0,12	690X1045X162
22,03	25,22	0,14	690X1245X162
14,20	16,55	0,09	790X645X162
17,99	20,72	0,11	790X845X162
21,77	24,86	0,14	790X1045X162
25,56	29,02	0,16	790X1245X162
16,13	18,65	0,10	890X645X162
20,44	23,37	0,13	890X845X162
24,76	28,09	0,16	890X1045X162
18,05	20,73	0,11	990X645X162
22,90	26,03	0,14	990X845X162
27,75	31,32	0,17	990X1045X162

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel