

ALBITE MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110101405750610	580 x 610	18	197	580				5	50	2.75	C
5110101405750720	580 x 720	22	197	690				5	50	3.09	C
5110101405750830	580 x 830	26	197	800				5	50	3.43	C
5110101405750940	580 x 940	30	197	910				5	50	3.77	C
5110101405751050	580 x 1050	34	197	1020				5	50	4.11	C
5110101405751160	580 x 1160	38	197	1130				5	50	4.45	C
5110101405751270	580 x 1270	42	197	1240				5	50	4.79	C
5110101405751380	580 x 1380	46	197	1350				5	50	5.12	C
5110101406750610	680 x 610	18	197	580				5	50	3.20	C
5110101406750720	680 x 720	22	197	690				5	50	3.59	C
5110101406750830	680 x 830	26	197	800				5	50	3.99	C
5110101406750940	680 x 940	30	197	910				5	50	4.39	C
5110101406751050	680 x 1050	34	197	1020				5	50	4.78	C
5110101407750610	780 x 610	18	197	580				5	50	3.64	C
5110101407750720	780 x 720	22	197	690				5	50	4.10	C
5110101407750830	780 x 830	26	197	800				5	50	4.55	C
5110101407750940	780 x 940	30	197	910				5	50	5.01	C
5110101407751050	780 x 1050	34	197	1020				5	50	5.46	C
5110101408750610	880 x 610	18	197	580				5	50	4.09	C
5110101408750720	880 x 720	22	197	690				5	50	4.60	C
5110101408750830	880 x 830	26	197	800				5	50	5.11	C
5110101408750940	880 x 940	30	197	910				5	50	5.62	C
5110101408751050	880 x 1050	34	197	1020				5	50	6.13	C

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	mm	Watt	Btu	Watt
5110101405750610	1458	4972	1895	6463
5110101405750720	2034	6936	2644	9017
5110101405750830	2688	9166	3494	11916
5110101405750940	3414	11641	4438	15134
5110101405751050	4572	15592	5944	20270
5110101405751160	5397	18405	7017	23927
5110101405751270	6485	22115	8431	28749
5110101405751380	7502	25581	9752	33255
5110101406750610	1458	4972	1895	6463
5110101406750720	2034	6936	2644	9017
5110101406750830	2688	9166	3494	11916
5110101406750940	3414	11641	4438	15134
5110101406751050	4572	15592	5944	20270
5110101407750610	1458	4972	1895	6463
5110101407750720	2034	6936	2644	9017
5110101407750830	2688	9166	3494	11916
5110101407750940	3414	11641	4438	15134
5110101407751050	4572	15592	5944	20270
5110101408750610	1458	4972	1895	6463
5110101408750720	2034	6936	2644	9017
5110101408750830	2688	9166	3494	11916
5110101408750940	3414	11641	4438	15134
5110101408751050	4572	15592	5944	20270

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
16,21	18,52	0,11	690X635X229
18,90	21,40	0,12	690X745X229
21,58	24,27	0,14	690X855X229
24,27	27,16	0,16	690X965X229
26,95	30,05	0,17	690X1075X229
29,64	32,93	0,19	690X1185X229
32,32	35,80	0,21	690X1295X229
35,01	38,68	0,23	690X1405X229
19,18	21,67	0,12	790X635X229
22,41	25,11	0,14	790X745X229
25,62	28,54	0,16	790X855X229
28,83	31,96	0,18	790X965X229
32,04	35,39	0,20	790X1075X229
22,16	24,82	0,13	890X635X229
25,91	28,82	0,16	890X745X229
29,65	32,78	0,18	890X855X229
33,40	36,77	0,20	890X965X229
37,14	40,74	0,22	890X1075X229
25,13	27,97	0,15	990X635X229
29,41	32,50	0,17	990X745X229
33,69	37,04	0,20	990X855X229
37,96	41,57	0,22	990X965X229
42,23	46,09	0,25	990X1075X229

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel