

FLAT MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110101505750615	580 x 620	10	120	585				6	35	2,33	C
5110101505750815	580 x 820	14	120	785				6	35	2,78	C
5110101505751015	580 x 1020	18	120	985				6	35	3,22	C
5110101505751215	580 x 1220	22	120	1185				6	35	3,66	C
5110101506750615	680 x 620	10	120	585				6	35	2,67	C
5110101506750815	680 x 820	14	120	785				6	35	3,17	C
5110101506751015	680 x 1020	18	120	985				6	35	3,67	C
5110101506751215	680 x 1220	22	120	1185				6	35	4,17	C
5110101507750615	780 x 620	10	120	585				6	35	3,00	C
5110101507750815	780 x 820	14	120	785				6	35	3,56	C
5110101507751015	780 x 1020	18	120	985				6	35	4,11	C
5110101508750615	880 x 620	10	120	585				6	35	3,33	C
5110101508750815	880 x 820	14	120	785				6	35	3,95	C
5110101508751015	880 x 1020	18	120	985				6	35	4,56	C

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5110101505750615	766	2613	996	3397
5110101505750815	1365	4656	1775	6053
5110101505751015	2097	7151	2726	9297
5110101505751215	2940	10025	3822	13033
5110101506750615	766	2613	996	3397
5110101506750815	1365	4656	1775	6053
5110101506751015	2097	7151	2726	9297
5110101506751215	2940	10025	3822	13033
5110101507750615	766	2613	996	3397
5110101507750815	1365	4656	1775	6053
5110101507751015	2097	7151	2726	9297
5110101508750615	766	2613	996	3397
5110101508750815	1365	4656	1775	6053
5110101508751015	2097	7151	2726	9297

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
12,42	14,57	0,07	690X640X152
15,68	18,16	0,09	690X840X152
18,94	21,75	0,11	690X1040X152
22,22	25,36	0,14	690X1240X152
14,38	16,70	0,08	790X640X152
18,17	20,86	0,11	790X840X152
21,97	25,02	0,13	790X1040X152
25,77	29,19	0,15	790X1240X152
16,33	18,82	0,09	890X640X152
20,66	23,55	0,12	890X840X152
24,99	28,29	0,15	890X1040X152
18,29	20,93	0,10	990X640X152
23,15	26,24	0,13	990X840X152
28,01	31,53	0,16	990X1040X152

C: Central Heating / E: Electric / D: Dual Fuel