

SERENO MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

| MODEL CODE       | Height x Width | Tube   | Depth (D) | Pipe Centers (A) | Wall to Pipe Centers (L) | Depth From Wall (K) | Wall To Radiator Back (M) | Space Between Tubes (E) | Tube Width (F) | Water Volume | Fuel Type |
|------------------|----------------|--------|-----------|------------------|--------------------------|---------------------|---------------------------|-------------------------|----------------|--------------|-----------|
|                  | mm             | pieces | mm        | mm               | mm                       | mm                  | mm                        | mm                      | mm             | L            |           |
| 5110101805750635 | 580 x 640      | 10     | 120       | 605              |                          |                     |                           | 4                       | 100            | 2.45         | C         |
| 5110101805750845 | 580 x 850      | 14     | 120       | 815              |                          |                     |                           | 4                       | 100            | 2.94         | C         |
| 5110101805751050 | 580 x 1050     | 18     | 120       | 1020             |                          |                     |                           | 4                       | 100            | 3.42         | C         |
| 5110101805751260 | 580 x 1260     | 22     | 120       | 1230             |                          |                     |                           | 4                       | 100            | 3.91         | C         |
| 5110101806750635 | 680 x 640      | 10     | 120       | 605              |                          |                     |                           | 4                       | 100            | 2.78         | C         |
| 5110101806750845 | 680 x 850      | 14     | 120       | 815              |                          |                     |                           | 4                       | 100            | 3.33         | C         |
| 5110101806751050 | 680 x 1050     | 18     | 120       | 1020             |                          |                     |                           | 4                       | 100            | 3.87         | C         |
| 5110101806751260 | 680 x 1260     | 22     | 120       | 1230             |                          |                     |                           | 4                       | 100            | 4.42         | C         |
| 5110101807750635 | 780 x 640      | 10     | 120       | 605              |                          |                     |                           | 4                       | 100            | 3.11         | C         |
| 5110101807750845 | 780 x 850      | 14     | 120       | 815              |                          |                     |                           | 4                       | 100            | 3.72         | C         |
| 5110101807751050 | 780 x 1050     | 18     | 120       | 1020             |                          |                     |                           | 4                       | 100            | 4.32         | C         |
| 5110101808750635 | 880 x 640      | 10     | 120       | 605              |                          |                     |                           | 4                       | 100            | 3.44         | C         |
| 5110101808750845 | 880 x 850      | 14     | 120       | 815              |                          |                     |                           | 4                       | 100            | 4.11         | C         |
| 5110101808751050 | 880 x 1050     | 18     | 120       | 1020             |                          |                     |                           | 4                       | 100            | 4.76         | C         |

CONNECTIONS TYPE

|    |    |    |    |    |    |
|----|----|----|----|----|----|
| SX | ZX | YP | YL | AX | P3 |
| x  | ✓  | ✓  | ✓  | ✓  | x  |

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

| MODEL CODE       | Heat Outputs ΔT 50 °C |      | Heat Outputs ΔT 60 °C |       |
|------------------|-----------------------|------|-----------------------|-------|
|                  | Watt                  | Btu  | Watt                  | Btu   |
| 5110101805750635 | 584                   | 1992 | 759                   | 2589  |
| 5110101805750845 | 1044                  | 3559 | 1357                  | 4627  |
| 5110101805751050 | 1746                  | 5952 | 2269                  | 7738  |
| 5110101805751260 | 2450                  | 8353 | 3184                  | 10859 |
| 5110101806750635 | 584                   | 1992 | 759                   | 2589  |
| 5110101806750845 | 1044                  | 3559 | 1357                  | 4627  |
| 5110101806751050 | 1746                  | 5952 | 2269                  | 7738  |
| 5110101806751260 | 2450                  | 8353 | 3184                  | 10859 |
| 5110101807750635 | 584                   | 1992 | 759                   | 2589  |
| 5110101807750845 | 1044                  | 3559 | 1357                  | 4627  |
| 5110101807751050 | 1746                  | 5952 | 2269                  | 7738  |
| 5110101808750635 | 584                   | 1992 | 759                   | 2589  |
| 5110101808750845 | 1044                  | 3559 | 1357                  | 4627  |
| 5110101808751050 | 1746                  | 5952 | 2269                  | 7738  |

LOGISTICS INFORMATION

| Net Weight | Gross Weight | Package Volume | Package Dimensions ( H x W x D ) |
|------------|--------------|----------------|----------------------------------|
| kg         | kg           | m³             | mm                               |
| 11.36      | 13.55        | 0.07           | 690X660X152                      |
| 14.26      | 16.80        | 0.10           | 690X870X152                      |
| 17.13      | 20.01        | 0.12           | 690X1075X152                     |
| 20.04      | 23.26        | 0.14           | 690X1285X152                     |
| 12.90      | 15.25        | 0.08           | 790X660X152                      |
| 16.17      | 18.91        | 0.11           | 790X870X152                      |
| 19.43      | 22.56        | 0.13           | 790X1075X152                     |
| 22.72      | 26.23        | 0.16           | 790X1285X152                     |
| 14.43      | 16.95        | 0.09           | 890X660X152                      |
| 18.09      | 21.04        | 0.12           | 890X870X152                      |
| 21.72      | 25.08        | 0.15           | 890X1075X152                     |
| 15.96      | 18.66        | 0.10           | 990X660X152                      |
| 20.00      | 23.15        | 0.14           | 990X870X152                      |
| 24.01      | 27.62        | 0.17           | 990X1075X152                     |

C: Central Heating / E: Electric / D: Dual Fuel