

SERRO MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110101905750635	580 x 640	10	120	605	57-83	72-98	44-70	4	100	2.40	C
5110101905750845	580 x 850	14	120	815	57-83	72-98	44-70	4	100	2.88	C
5110101905751050	580 x 1050	18	120	1020	57-83	72-98	44-70	4	100	3.34	C
5110101905751260	580 x 1260	22	120	1230	57-83	72-98	44-70	4	100	3.82	C
5110101906750635	680 x 640	10	120	605	57-83	72-98	44-70	4	100	2.74	C
5110101906750845	680 x 850	14	120	815	57-83	72-98	44-70	4	100	3.27	C
5110101906751050	680 x 1050	18	120	1020	57-83	72-98	44-70	4	100	3.79	C
5110101906751260	680 x 1260	22	120	1230	57-83	72-98	44-70	4	100	4.32	C
5110101907750635	780 x 640	10	120	605	57-83	72-98	44-70	4	100	3.07	C
5110101907750845	780 x 850	14	120	815	57-83	72-98	44-70	4	100	3.66	C
5110101907751050	780 x 1050	18	120	1020	57-83	72-98	44-70	4	100	4.24	C
5110101908750635	880 x 640	10	120	605	57-83	72-98	44-70	4	100	3.40	C
5110101908750845	880 x 850	14	120	815	57-83	72-98	44-70	4	100	4.05	C
5110101908751050	880 x 1050	18	120	1020	57-83	72-98	44-70	4	100	4.69	C

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		
	mm	Watt	Btu	Watt	Btu
5110101905750635	584	1992	759	2589	
5110101905750845	1044	3559	1357	4627	
5110101905751050	1746	5952	2269	7738	
5110101905751260	2450	8353	3184	10859	
5110101906750635	584	1992	759	2589	
5110101906750845	1044	3559	1357	4627	
5110101906751050	1746	5952	2269	7738	
5110101906751260	2450	8353	3184	10859	
5110101907750635	584	1992	759	2589	
5110101907750845	1044	3559	1357	4627	
5110101907751050	1746	5952	2269	7738	
5110101908750635	584	1992	759	2589	
5110101908750845	1044	3559	1357	4627	
5110101908751050	1746	5952	2269	7738	

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
11.08	13.27	0.07	690X660X152
13.86	16.40	0.10	690X870X152
16.62	19.50	0.12	690X1075X152
19.42	22.64	0.14	690X1285X152
12.61	14.96	0.08	790X660X152
15.78	18.52	0.11	790X870X152
18.92	22.05	0.13	790X1075X152
22.09	25.60	0.16	790X1285X152
14.15	16.67	0.09	890X660X152
17.69	20.64	0.12	890X870X152
21.21	24.57	0.15	890X1075X152
15.68	18.38	0.10	990X660X152
19.60	22.75	0.14	990X870X152
23.50	27.11	0.17	990X1075X152

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel