

TRIO MAX

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Height x Width	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5110102105750420	580 x 420	14	120	390				15	30	2.20	C
5110102105750510	580 x 510	18	120	480				15	30	2.48	C
5110102105750600	580 x 600	22	120	570				15	30	2.77	C
5110102105750690	580 x 690	26	120	660				15	30	3.05	C
5110102105750780	580 x 780	30	120	750				15	30	3.33	C
5110102105750870	580 x 870	34	120	840				15	30	3.61	C
5110102105750960	580 x 960	38	120	930				15	30	3.89	C
5110102105751050	580 x 1050	42	120	1020				15	30	4.18	C
5110102105751140	580 x 1140	46	120	1110				15	30	4.46	C
5110102105751230	580 x 1230	50	120	1200				15	30	4.74	C
5110102105751320	580 x 1320	54	120	1290				15	30	5.02	C
5110102106750420	680 x 420	14	120	390				15	30	2.59	C
5110102106750510	680 x 510	18	120	480				15	30	2.93	C
5110102106750600	680 x 600	22	120	570				15	30	3.27	C
5110102106750690	680 x 690	26	120	660				15	30	3.61	C
5110102106750780	680 x 780	30	120	750				15	30	3.95	C
5110102106750870	680 x 870	34	120	840				15	30	4.29	C
5110102106750960	680 x 960	38	120	930				15	30	4.63	C
5110102106751050	680 x 1050	42	120	1020				15	30	4.97	C
5110102106751140	680 x 1140	46	120	1110				15	30	5.31	C
5110102106751230	680 x 1230	50	120	1200				15	30	5.64	C
5110102106751320	680 x 1320	54	120	1290				15	30	5.98	C
5110102107750420	780 x 420	14	120	390				15	30	2.98	C
5110102107750510	780 x 510	18	120	480				15	30	3.38	C
5110102107750600	780 x 600	22	120	570				15	30	3.77	C
5110102107750690	780 x 690	26	120	660				15	30	4.17	C
5110102107750780	780 x 780	30	120	750				15	30	4.57	C
5110102107750870	780 x 870	34	120	840				15	30	4.96	C
5110102107750960	780 x 960	38	120	930				15	30	5.36	C
5110102107751050	780 x 1050	42	120	1020				15	30	5.76	C
5110102108750420	880 x 420	14	120	390				15	30	3.37	C
5110102108750510	880 x 510	18	120	480				15	30	3.82	C
5110102108750600	880 x 600	22	120	570				15	30	4.28	C
5110102108750690	880 x 690	26	120	660				15	30	4.73	C
5110102108750780	880 x 780	30	120	750				15	30	5.19	C
5110102108750870	880 x 870	34	120	840				15	30	5.64	C
5110102108750960	880 x 960	38	120	930				15	30	6.09	C
5110102108751050	880 x 1050	42	120	1020				15	30	6.55	C

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	mm	Watt	Btu	Btu
5110102105750420	285	972	371	1263
5110102105750510	468	1596	609	2075
5110102105750600	702	2393	912	3111
5110102105750690	947	3228	1231	4197
5110102105750780	1221	4165	1588	5415
5110102105750870	1524	5196	1981	6755
5110102105750960	1851	6313	2407	8207
5110102105751050	2224	7585	2892	9861
5110102105751140	2436	8308	3167	10800
5110102105751230	2797	9537	3636	12399
5110102105751320	3284	11198	4269	14557
5110102106750420	285	972	371	1263
5110102106750510	468	1596	609	2075
5110102106750600	702	2393	912	3111
5110102106750690	947	3228	1231	4197
5110102106750780	1221	4165	1588	5415
5110102106750870	1524	5196	1981	6755
5110102106750960	1851	6313	2407	8207
5110102106751050	2224	7585	2892	9861
5110102106751140	2436	8308	3167	10800
5110102106751230	2797	9537	3636	12399
5110102106751320	3284	11198	4269	14557
5110102107750420	285	972	371	1263
5110102107750510	468	1596	609	2075
5110102107750600	702	2393	912	3111
5110102107750690	947	3228	1231	4197
5110102107750780	1221	4165	1588	5415
5110102107750870	1524	5196	1981	6755
5110102107750960	1851	6313	2407	8207
5110102107751050	2224	7585	2892	9861
5110102108750420	285	972	371	1263
5110102108750510	468	1596	609	2075
5110102108750600	702	2393	912	3111
5110102108750690	947	3228	1231	4197
5110102108750780	1221	4165	1588	5415
5110102108750870	1524	5196	1981	6755
5110102108750960	1851	6313	2407	8207
5110102108751050	2224	7585	2892	9861

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
9.40	11.22	0.05	690X445X152
10.91	12.89	0.06	690X535X152
12.44	14.56	0.07	690X625X152
13.95	16.23	0.08	690X715X152
15.47	17.89	0.09	690X805X152
16.98	19.56	0.10	690X895X152
18.51	21.24	0.11	690X985X152
20.03	22.91	0.12	690X1075X152
21.54	24.57	0.13	690X1165X152
23.07	26.24	0.14	690X1255X152
24.58	27.90	0.15	690X1345X152
11.00	12.96	0.06	790X445X152
12.81	14.94	0.07	790X535X152
14.62	16.92	0.08	790X625X152
16.43	18.88	0.09	790X715X152
18.24	20.86	0.10	790X805X152
20.04	22.82	0.11	790X895X152
21.86	24.81	0.12	790X985X152
23.67	26.80	0.13	790X1075X152
25.47	28.75	0.14	790X1165X152
27.29	30.74	0.16	790X1255X152
29.09	32.70	0.17	790X1345X152
12.60	14.69	0.07	890X445X152
14.70	16.96	0.08	890X535X152
16.81	19.27	0.09	890X625X152
18.91	21.54	0.10	890X715X152
21.00	23.82	0.11	890X805X152
23.10	26.10	0.13	890X895X152
25.21	28.38	0.14	890X985X152
27.31	30.67	0.15	890X1075X152
14.21	16.43	0.07	990X445X152
16.60	19.01	0.09	990X535X152
18.99	21.61	0.10	990X625X152
21.38	24.20	0.11	990X715X152
23.77	26.79	0.13	990X805X152
26.16	29.37	0.14	990X895X152
28.56	31.96	0.15	990X985X152
30.95	34.56	0.17	990X1075X152

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
x	✓	✓	✓	✓	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel