

LODOS LINE W

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5130107903000750	300 x 750	8 (2+2)	31	255	70-90	80-105	54-74	21	158	1,53	1,53	C-E-D
5130107903001000	300 x 1000	10 (2+2)	31	255	70-90	80-105	54-74	21	166	2,01	2,01	C-E-D
5130107903001250	300 x 1250	12 (2+2)	31	255	70-90	80-105	54-74	21	171	2,48	2,48	C-E-D
5130107903001500	300 x 1500	14 (2+2)	31	255	70-90	80-105	54-74	21	174	2,95	2,95	C-E-D
5130107903001700	300 x 1700	16 (2+2)	31	255	70-90	80-105	54-74	21	170	3,35	3,35	C-E-D
5130107904000750	400 x 750	8 (2+2)	31	355	70-90	80-105	54-74	21	158	1,70	1,7	C-E-D
5130107904001000	400 x 1000	10 (2+2)	31	355	70-90	80-105	54-74	21	166	2,22	2,22	C-E-D
5130107904001250	400 x 1250	12 (2+2)	31	355	70-90	80-105	54-74	21	171	2,73	2,73	C-E-D
5130107904001500	400 x 1500	14 (2+2)	31	355	70-90	80-105	54-74	21	174	3,25	3,25	C-E-D
5130107904001700	400 x 1700	16 (2+2)	31	355	70-90	80-105	54-74	21	170	3,69	3,69	C-E-D
5130107905000750	500 x 750	8 (2+2)	31	455	70-90	80-105	54-74	21	158	1,87	1,87	C-E-D
5130107905001000	500 x 1000	10 (2+2)	31	455	70-90	80-105	54-74	21	166	2,43	2,43	C-E-D
5130107905001250	500 x 1250	12 (2+2)	31	455	70-90	80-105	54-74	21	171	2,98	2,98	C-E-D
5130107905001500	500 x 1500	14 (2+2)	31	455	70-90	80-105	54-74	21	174	3,54	3,54	C-E-D
5130107905001700	500 x 1700	16 (2+2)	31	455	70-90	80-105	54-74	21	170	4,02	4,02	C-E-D
5130107906000750	600 x 750	8 (2+2)	31	555	70-90	80-105	54-74	21	158	2,04	2,04	C-E-D
5130107906001000	600 x 1000	10 (2+2)	31	555	70-90	80-105	54-74	21	166	2,64	2,64	C-E-D
5130107906001250	600 x 1250	12 (2+2)	31	555	70-90	80-105	54-74	21	171	3,24	3,24	C-E-D
5130107906001500	600 x 1500	14 (2+2)	31	555	70-90	80-105	54-74	21	174	3,84	3,84	C-E-D
5130107906001700	600 x 1700	16 (2+2)	31	555	70-90	80-105	54-74	21	170	4,36	4,36	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5130107903000750	126	430	164	560
5130107903001000	164	560	214	730
5130107903001250	201	686	262	894
5130107903001500	238	812	310	1058
5130107903001700	271	925	353	1204
5130107904000750	152	519	198	676
5130107904001000	196	669	255	870
5130107904001250	240	819	312	1064
5130107904001500	283	966	368	1255
5130107904001700	322	1099	419	1429
5130107905000750	179	611	233	795
5130107905001000	230	785	299	1020
5130107905001250	280	955	364	1242
5130107905001500	330	1126	429	1463
5130107905001700	376	1283	489	1668
5130107906000750	207	706	270	921
5130107906001000	265	904	345	1177
5130107906001250	322	1099	419	1429
5130107906001500	380	1296	494	1685
5130107906001700	432	1474	562	1917

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5130107903000750	1,5	2,1	0,02	850 x 340 x 55
5130107903001000	1,8	2,6	0,03	1100 x 340 x 55
5130107903001250	2,1	3,1	0,03	1350 x 340 x 55
5130107903001500	2,4	3,8	0,03	1600 x 340 x 55
5130107903001700	2,7	4,3	0,04	1800 x 340 x 55
5130107904000750	1,6	2,4	0,03	850 x 440 x 55
5130107904001000	2	3	0,03	1100 x 440 x 55
5130107904001250	2,3	3,5	0,04	1350 x 440 x 55
5130107904001500	2,7	4,4	0,06	1600 x 440 x 85
5130107904001700	3	5	0,07	1800 x 440 x 85
5130107905000750	1,8	2,7	0,04	850 x 540 x 85
5130107905001000	2,2	3,4	0,06	1100 x 540 x 85
5130107905001250	2,5	4	0,07	1350 x 540 x 85
5130107905001500	2,9	3,9	0,05	1600 x 540 x 55
5130107905001700	3,3	4,4	0,06	1800 x 540 x 55
5130107906000750	1,9	2,4	0,03	850 x 640 x 55
5130107906001000	2,3	3	0,04	1100 x 640 x 55
5130107906001250	2,8	3,6	0,05	1350 x 640 x 55
5130107906001500	3,2	4,4	0,06	1600 x 640 x 55
5130107906001700	3,6	4,9	0,07	1800 x 640 x 55