

LODOS PLUS W

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5130108103000800	300 x 800	14 (3+5+6)	31	255	70-90	80-105	54-74	21	131	1,90	1,9	C-E-D
5130108103001000	300 x 1000	18 (4+6+8)	31	255	70-90	80-105	54-74	21	151	2,40	2,4	C-E-D
5130108103001200	300 x 1200	21 (4+5+6+6)	31	255	70-90	80-105	54-74	21	134	2,84	2,84	C-E-D
5130108103001450	300 x 1450	28 (4+6+8+10)	31	255	70-90	80-105	54-74	21	124	3,56	3,56	C-E-D
5130108103001700	300 x 1700	30 (4+5+6+7+8)	31	255	70-90	80-105	54-74	21	141	4,03	4,03	C-E-D
5130108104000800	400 x 800	14 (3+5+6)	31	355	70-90	80-105	54-74	21	131	2,19	2,19	C-E-D
5130108104001000	400 x 1000	18 (4+6+8)	31	355	70-90	80-105	54-74	21	151	2,77	2,77	C-E-D
5130108104001200	400 x 1200	21 (4+5+6+6)	31	355	70-90	80-105	54-74	21	134	3,28	3,28	C-E-D
5130108104001450	400 x 1450	28 (4+6+8+10)	31	355	70-90	80-105	54-74	21	124	4,15	4,15	C-E-D
5130108104001700	400 x 1700	30 (4+5+6+7+8)	31	355	70-90	80-105	54-74	21	141	4,66	4,66	C-E-D
5130108105000800	500 x 800	14 (3+5+6)	31	455	70-90	80-105	54-74	21	131	2,49	2,49	C-E-D
5130108105001000	500 x 1000	18 (4+6+8)	31	455	70-90	80-105	54-74	21	151	3,15	3,15	C-E-D
5130108105001200	500 x 1200	21 (4+5+6+6)	31	455	70-90	80-105	54-74	21	134	3,72	3,72	C-E-D
5130108105001450	500 x 1450	28 (4+6+8+10)	31	455	70-90	80-105	54-74	21	124	4,73	4,73	C-E-D
5130108105001700	500 x 1700	30 (4+5+6+7+8)	31	455	70-90	80-105	54-74	21	141	5,29	5,29	C-E-D
5130108106000800	600 x 800	14 (3+5+6)	31	555	70-90	80-105	54-74	21	131	2,78	2,78	C-E-D
5130108106001000	600 x 1000	18 (4+6+8)	31	555	70-90	80-105	54-74	21	151	3,53	3,53	C-E-D
5130108106001200	600 x 1200	21 (4+5+6+6)	31	555	70-90	80-105	54-74	21	134	4,17	4,17	C-E-D
5130108106001450	600 x 1450	28 (4+6+8+10)	31	555	70-90	80-105	54-74	21	124	5,32	5,32	C-E-D
5130108106001700	600 x 1700	30 (4+5+6+7+8)	31	555	70-90	80-105	54-74	21	141	5,92	5,92	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5130108103000800	174	594	227	775
5130108103001000	221	754	288	983
5130108103001200	261	891	340	1160
5130108103001450	334	1139	435	1484
5130108103001700	371	1266	483	1648
5130108104000800	219	747	285	972
5130108104001000	279	952	363	1238
5130108104001200	329	1122	428	1460
5130108104001450	424	1446	552	1883
5130108104001700	468	1596	609	2077
5130108105000800	266	908	346	1180
5130108105001000	340	1160	442	1508
5130108105001200	399	1361	519	1770
5130108105001450	518	1767	674	2299
5130108105001700	569	1941	740	2524
5130108106000800	315	1075	410	1399
5130108106001000	403	1375	524	1787
5130108106001200	473	1613	615	2098
5130108106001450	617	2104	803	2739
5130108106001700	674	2299	877	2991

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5130108103000800	1,8	2,4	0,02	900 x 340 x 55
5130108103001000	2,1	3	0,03	1100 x 340 x 55
5130108103001200	2,4	3,4	0,03	1300 x 340 x 55
5130108103001450	3	4,4	0,03	1550 x 340 x 55
5130108103001700	3,3	4,9	0,04	1800 x 340 x 55
5130108104000800	2	2,9	0,03	900 x 440 x 55
5130108104001000	2,5	3,5	0,03	1100 x 440 x 55
5130108104001200	2,8	4	0,04	1300 x 440 x 55
5130108104001450	3,5	5,2	0,06	1550 x 440 x 85
5130108104001700	3,9	5,8	0,07	1800 x 440 x 85
5130108105000800	2,3	3,3	0,05	900 x 540 x 85
5130108105001000	2,8	4	0,06	1100 x 540 x 85
5130108105001200	3,2	4,7	0,06	1300 x 540 x 85
5130108105001450	4,1	5	0,05	1550 x 540 x 55
5130108105001700	4,4	5,5	0,06	1800 x 540 x 55
5130108106000800	2,6	3,1	0,04	900 x 640 x 55
5130108106001000	3,2	3,8	0,04	1100 x 640 x 55
5130108106001200	3,6	4,6	0,05	1300 x 640 x 55
5130108106001450	4,6	5,7	0,06	1550 x 640 x 55
5130108106001700	5	6,3	0,07	1800 x 640 x 55