

LODOS STYLE W

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5130108303000700	300 x 700	6 (2+1+1+2)	31	255	70-90	80-105	54-74	21	168	1,36	1,36	C-E-D
5130108303001000	300 x 1000	6 (2+1+1+2)	31	255	70-90	80-105	54-74	21	153	1,91	1,91	C-E-D
5130108303001200	300 x 1200	6 (2+1+1+2)	31	255	70-90	80-105	54-74	21	132	2,31	2,31	C-E-D
5130108303001400	300 x 1400	6 (2+1+1+2)	31	255	70-90	80-105	54-74	21	121	2,71	2,71	C-E-D
5130108303001700	300 x 1700	6 (2+1+1+2)	31	255	70-90	80-105	54-74	21	123	3,26	3,26	C-E-D
5130108304000700	400 x 700	6 (2+1+1+2)	31	355	70-90	80-105	54-74	21	168	1,49	1,49	C-E-D
5130108304001000	400 x 1000	6 (2+1+1+2)	31	355	70-90	80-105	54-74	21	153	2,08	2,08	C-E-D
5130108304001200	400 x 1200	6 (2+1+1+2)	31	355	70-90	80-105	54-74	21	132	2,52	2,52	C-E-D
5130108304001400	400 x 1400	6 (2+1+1+2)	31	355	70-90	80-105	54-74	21	121	2,96	2,96	C-E-D
5130108304001700	400 x 1700	6 (2+1+1+2)	31	355	70-90	80-105	54-74	21	123	3,55	3,55	C-E-D
5130108305000700	500 x 700	6 (2+1+1+2)	31	455	70-90	80-105	54-74	21	168	1,61	1,61	C-E-D
5130108305001000	500 x 1000	6 (2+1+1+2)	31	455	70-90	80-105	54-74	21	153	2,25	2,25	C-E-D
5130108305001200	500 x 1200	6 (2+1+1+2)	31	455	70-90	80-105	54-74	21	132	2,73	2,73	C-E-D
5130108305001400	500 x 1400	6 (2+1+1+2)	31	455	70-90	80-105	54-74	21	121	3,21	3,21	C-E-D
5130108305001700	500 x 1700	6 (2+1+1+2)	31	455	70-90	80-105	54-74	21	123	3,84	3,84	C-E-D
5130108306000700	600 x 700	6 (2+1+1+2)	31	555	70-90	80-105	54-74	21	168	1,74	1,74	C-E-D
5130108306001000	600 x 1000	6 (2+1+1+2)	31	555	70-90	80-105	54-74	21	153	2,41	2,41	C-E-D
5130108306001200	600 x 1200	6 (2+1+1+2)	31	555	70-90	80-105	54-74	21	132	2,94	2,94	C-E-D
5130108306001400	600 x 1400	6 (2+1+1+2)	31	555	70-90	80-105	54-74	21	121	3,46	3,46	C-E-D
5130108306001700	600 x 1700	6 (2+1+1+2)	31	555	70-90	80-105	54-74	21	123	4,14	4,14	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5130108303000700	108	369	141	481
5130108303001000	149	509	194	662
5130108303001200	182	621	237	809
5130108303001400	215	734	280	955
5130108303001700	256	873	333	1136
5130108304000700	127	434	166	567
5130108304001000	175	597	228	778
5130108304001200	214	730	279	952
5130108304001400	253	863	329	1122
5130108304001700	302	1030	393	1341
5130108305000700	147	502	192	655
5130108305001000	202	689	263	897
5130108305001200	248	846	323	1102
5130108305001400	294	1003	383	1307
5130108305001700	349	1191	454	1549
5130108306000700	168	573	219	747
5130108306001000	230	785	299	1020
5130108306001200	283	966	368	1255
5130108306001400	336	1146	437	1491
5130108306001700	398	1358	518	1767

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5130108303000700	1,3	1,9	0,02	800 x 340 x 55
5130108303001000	1,7	2,5	0,03	1100 x 340 x 55
5130108303001200	2	2,7	0,03	1300 x 340 x 55
5130108303001400	2,2	3,6	0,03	1500 x 340 x 55
5130108303001700	2,6	4,6	0,06	1800 x 340 x 85
5130108304000700	1,4	2,2	0,02	800 x 440 x 55
5130108304001000	1,8	2,8	0,03	1100 x 440 x 55
5130108304001200	2,1	3,3	0,04	1300 x 440 x 55
5130108304001400	2,5	4,1	0,06	1500 x 440 x 85
5130108304001700	2,9	4,5	0,05	1800 x 440 x 55
5130108305000700	1,6	2,5	0,04	800 x 540 x 85
5130108305001000	2	3,2	0,06	1100 x 540 x 85
5130108305001200	2,3	3,8	0,06	1300 x 540 x 85
5130108305001400	2,7	3,6	0,05	1500 x 540 x 55
5130108305001700	3,1	4,2	0,06	1800 x 540 x 55
5130108306000700	1,7	2,2	0,03	800 x 640 x 55
5130108306001000	2,1	2,8	0,04	1100 x 640 x 55
5130108306001200	2,5	3,5	0,05	1300 x 640 x 55
5130108306001400	2,9	4	0,06	1500 x 640 x 55
5130108306001700	3,4	4,7	0,07	1800 x 640 x 55