

OXY

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5130111004000460	400 x 460	2 (1+1)	80	50	58-83	112-138	43-68			1,65	1,65	C-E-D
5130111004000730	400 x 730	3 (1+1)	80	50	58-83	112-138	43-68			2,54	2,54	C-E-D
5130111004001000	400 x 1000	4 (1+1)	80	50	58-83	112-138	43-68			3,42	3,42	C-E-D
5130111004001270	400 x 1270	5 (1+1)	80	50	58-83	112-138	43-68			4,31	4,31	C-E-D
5130111004001540	400 x 1540	6 (1+1)	80	50	58-83	112-138	43-68			5,19	5,19	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5130111004000460	118	403	154	526
5130111004000730	183	625	238	812
5130111004001000	247	843	322	1099
5130111004001270	311	1061	405	1382
5130111004001540	376	1283	489	1668

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5130111004000460	1,6	2,1	0,03	560 x 440 x 110
5130111004000730	2,3	3,1	0,05	830 x 440 x 110
5130111004001000	3	4	0,06	1100 x 440 x 110
5130111004001270	3,8	4,9	0,07	1370 x 440 x 110
5130111004001540	4,5	5,9	0,08	1640 x 440 x 110