

PRUSIAS

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5130113704000700	400 x 700	3 (1+1)	120	50	59-85	534-560	44-70			0,90	0,9	C-E-D
5130113704001000	400 x 1000	4 (1+1)	120	50	59-85	534-560	44-70			1,23	1,23	C-E-D
5130113704001200	400 x 1200	5 (1+1)	120	50	59-85	534-560	44-70			1,51	1,51	C-E-D
5130113704001400	400 x 1400	6 (1+1)	120	50	59-85	534-560	44-70			1,79	1,79	C-E-D
5130113704001600	400 x 1600	7 (1+1)	120	50	59-85	534-560	44-70			2,07	2,07	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5130113704000700	275	938	358	1221
5130113704001000	385	1313	501	1709
5130113704001200	467	1593	608	2074
5130113704001400	549	1873	714	2435
5130113704001600	632	2156	822	2804

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5130113704000700	2,9	3,7	0,05	800 x 440 x 140
5130113704001000	3,9	5	0,07	1100 x 440 x 140
5130113704001200	4,7	5,9	0,09	1300 x 440 x 140
5130113704001400	5,5	6,8	0,1	1500 x 440 x 140
5130113704001600	6,2	7,7	0,11	1700 x 440 x 140