

VIOLA LINE W

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5130128403000700	300 x 700	6 (2+2)	31	255	71-91	86-106	56-76	15	157	1,03	1,03	C-E-D
5130128403001000	300 x 1000	8 (2+2)	31	255	71-91	86-106	56-76	15	167	1,46	1,46	C-E-D
5130128403001250	300 x 1250	10 (2+2)	31	255	71-91	86-106	56-76	15	159	1,83	1,83	C-E-D
5130128403001550	300 x 1550	12 (2+2)	31	255	71-91	86-106	56-76	15	164	2,26	2,26	C-E-D
5130128403001700	300 x 1700	14 (2+2)	31	255	71-91	86-106	56-76	15	142	2,48	2,48	C-E-D
5130128404000700	400 x 700	6 (2+2)	31	355	71-91	86-106	56-76	15	157	1,03	1,03	C-E-D
5130128404001000	400 x 1000	8 (2+2)	31	355	71-91	86-106	56-76	15	167	1,46	1,46	C-E-D
5130128404001250	400 x 1250	10 (2+2)	31	355	71-91	86-106	56-76	15	159	1,83	1,83	C-E-D
5130128404001550	400 x 1550	12 (2+2)	31	355	71-91	86-106	56-76	15	164	2,26	2,26	C-E-D
5130128404001700	400 x 1700	14 (2+2)	31	355	71-91	86-106	56-76	15	142	2,48	2,48	C-E-D
5130128405000700	500 x 700	6 (2+2)	31	455	71-91	86-106	56-76	15	157	1,03	1,03	C-E-D
5130128405001000	500 x 1000	8 (2+2)	31	455	71-91	86-106	56-76	15	167	1,46	1,46	C-E-D
5130128405001250	500 x 1250	10 (2+2)	31	455	71-91	86-106	56-76	15	159	1,83	1,83	C-E-D
5130128405001550	500 x 1550	12 (2+2)	31	455	71-91	86-106	56-76	15	164	2,26	2,26	C-E-D
5130128405001700	500 x 1700	14 (2+2)	31	455	71-91	86-106	56-76	15	142	2,48	2,48	C-E-D
5130128406000700	600 x 700	6 (2+2)	31	555	71-91	86-106	56-76	15	157	1,03	1,03	C-E-D
5130128406001000	600 x 1000	8 (2+2)	31	555	71-91	86-106	56-76	15	167	1,46	1,46	C-E-D
5130128406001250	600 x 1250	10 (2+2)	31	555	71-91	86-106	56-76	15	159	1,83	1,83	C-E-D
5130128406001550	600 x 1550	12 (2+2)	31	555	71-91	86-106	56-76	15	164	2,26	2,26	C-E-D
5130128406001700	600 x 1700	14 (2+2)	31	555	71-91	86-106	56-76	15	142	2,48	2,48	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5130128403000700	162	553	211	720
5130128403001000	223	761	290	989
5130128403001250	278	948	362	1235
5130128403001550	338	1153	440	1501
5130128403001700	384	1310	500	1705
5130128404000700	208	710	271	925
5130128404001000	283	966	368	1255
5130128404001250	354	1208	461	1573
5130128404001550	429	1463	558	1903
5130128404001700	491	1675	639	2179
5130128405000700	255	870	332	1133
5130128405001000	346	1180	450	1535
5130128405001250	433	1477	563	1920
5130128405001550	524	1787	682	2326
5130128405001700	601	2050	782	2667
5130128406000700	305	1041	397	1354
5130128406001000	412	1405	536	1828
5130128406001250	515	1757	670	2285
5130128406001550	623	2125	810	2763
5130128406001700	716	2442	931	3175

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5130128403000700	1,6	2,2	0,02	800 x 440 x 55
5130128403001000	2	2,8	0,03	1100 x 440 x 55
5130128403001250	2,4	3,4	0,04	1350 x 440 x 55
5130128403001550	2,9	4,4	0,05	1650 x 540 x 55
5130128403001700	3,2	4,8	0,06	1800 x 540 x 55
5130128404000700	1,8	2,5	0,03	800 x 540 x 55
5130128404001000	2,3	3,3	0,04	1100 x 540 x 55
5130128404001250	2,8	4	0,05	1350 x 540 x 55
5130128404001550	3,4	5,2	0,09	1650 x 640 x 85
5130128404001700	3,8	5,7	0,1	1800 x 640 x 85
5130128405000700	2	3	0,05	800 x 640 x 85
5130128405001000	2,7	3,9	0,06	1100 x 640 x 85
5130128405001250	3,2	4,7	0,08	1350 x 640 x 85
5130128405001550	3,9	4,8	0,04	1650 x 340 x 55
5130128405001700	4,3	5,4	0,04	1800 x 340 x 55
5130128406000700	2,3	2,8	0,02	800 x 340 x 55
5130128406001000	3	3,6	0,03	1100 x 340 x 55
5130128406001250	3,6	4,4	0,03	1350 x 340 x 55
5130128406001550	4,3	5,6	0,04	1650 x 440 x 55
5130128406001700	4,9	6,2	0,05	1800 x 440 x 55