

VIOLA PLUS W

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5130130203000750	300 x 750	9 (3+6)	31	255	71-91	86-106	56-76	15	154	1,10	1,1	C-E-D
5130130203001050	300 x 1050	12 (3+4+5)	31	255	71-91	86-106	56-76	15	137	1,54	1,54	C-E-D
5130130203001300	300 x 1300	15 (4+5+6)	31	255	71-91	86-106	56-76	15	165	1,90	1,9	C-E-D
5130130203001649	300 x 1649	18 (4+4+5+5)	31	255	71-91	86-106	56-76	15	167	2,41	2,41	C-E-D
5130130203001700	300 x 1700	20 (4+4+5+7)	31	255	71-91	86-106	56-76	15	140	2,48	2,48	C-E-D
5130130204000750	400 x 750	9 (3+6)	31	355	71-91	86-106	56-76	15	154	1,10	1,1	C-E-D
5130130204001050	400 x 1050	12 (3+4+5)	31	355	71-91	86-106	56-76	15	137	1,54	1,54	C-E-D
5130130204001300	400 x 1300	15 (4+5+6)	31	355	71-91	86-106	56-76	15	165	1,90	1,9	C-E-D
5130130204001649	400 x 1649	18 (4+4+5+5)	31	355	71-91	86-106	56-76	15	167	2,41	2,41	C-E-D
5130130204001700	400 x 1700	20 (4+4+5+7)	31	355	71-91	86-106	56-76	15	140	2,48	2,48	C-E-D
5130130205000750	500 x 750	9 (3+6)	31	455	71-91	86-106	56-76	15	154	1,10	1,1	C-E-D
5130130205001050	500 x 1050	12 (3+4+5)	31	455	71-91	86-106	56-76	15	137	1,54	1,54	C-E-D
5130130205001300	500 x 1300	15 (4+5+6)	31	455	71-91	86-106	56-76	15	165	1,90	1,9	C-E-D
5130130205001649	500 x 1649	18 (4+4+5+5)	31	455	71-91	86-106	56-76	15	167	2,41	2,41	C-E-D
5130130205001700	500 x 1700	20 (4+4+5+7)	31	455	71-91	86-106	56-76	15	140	2,48	2,48	C-E-D
5130130206000750	600 x 750	9 (3+6)	31	555	71-91	86-106	56-76	15	154	1,10	1,1	C-E-D
5130130206001050	600 x 1050	12 (3+4+5)	31	555	71-91	86-106	56-76	15	137	1,54	1,54	C-E-D
5130130206001300	600 x 1300	15 (4+5+6)	31	555	71-91	86-106	56-76	15	165	1,90	1,9	C-E-D
5130130206001649	600 x 1649	18 (4+4+5+5)	31	555	71-91	86-106	56-76	15	167	2,41	2,41	C-E-D
5130130206001700	600 x 1700	20 (4+4+5+7)	31	555	71-91	86-106	56-76	15	140	2,48	2,48	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5130130203000750	216	737	281	959
5130130203001050	292	996	380	1296
5130130203001300	364	1242	474	1617
5130130203001649	445	1518	579	1975
5130130203001700	482	1644	627	2139
5130130204000750	284	969	370	1262
5130130204001050	383	1307	498	1699
5130130204001300	478	1630	622	2122
5130130204001649	581	1982	756	2578
5130130204001700	634	2162	825	2814
5130130205000750	355	1211	462	1576
5130130205001050	478	1630	622	2122
5130130205001300	596	2033	775	2643
5130130205001649	723	2466	940	3206
5130130205001700	792	2701	1030	3513
5130130206000750	429	1463	558	1903
5130130206001050	577	1968	751	2561
5130130206001300	720	2456	936	3192
5130130206001649	872	2974	1134	3867
5130130206001700	956	3260	1243	4239

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5130130203000750	1,9	2,5	0,03	850 x 440 x 55
5130130203001050	2,4	3,3	0,03	1150 x 440 x 55
5130130203001300	2,9	4	0,04	1400 x 440 x 55
5130130203001649	3,5	5,1	0,06	1749 x 540 x 55
5130130203001700	3,8	5,4	0,06	1800 x 540 x 55
5130130204000750	2,2	3	0,03	850 x 540 x 55
5130130204001050	2,9	3,9	0,04	1150 x 540 x 55
5130130204001300	3,5	4,8	0,05	1400 x 540 x 55
5130130204001649	4,3	6,2	0,1	1749 x 640 x 85
5130130204001700	4,6	6,5	0,1	1800 x 640 x 85
5130130205000750	2,6	3,6	0,05	850 x 640 x 85
5130130205001050	3,4	4,7	0,07	1150 x 640 x 85
5130130205001300	4,1	5,7	0,08	1400 x 640 x 85
5130130205001649	5	6	0,04	1749 x 340 x 55
5130130205001700	5,4	6,4	0,04	1800 x 340 x 55
5130130206000750	3	3,5	0,02	850 x 340 x 55
5130130206001050	3,9	4,6	0,03	1150 x 340 x 55
5130130206001300	4,8	5,6	0,03	1400 x 340 x 55
5130130206001649	5,7	6,7	0,04	1749 x 340 x 55
5130130206001700	6,2	7,5	0,05	1800 x 440 x 55