

POYRAZ LINE W

TECHNICAL INFORMATION

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L	
5130131703000700	300 x 700	6 (2+2)	30	255	70-90	85-105	55-75	15	172	1,03	1,03	C-E-D
5130131703001000	300 x 1000	8 (2+2)	30	255	70-90	85-105	55-75	15	180	1,46	1,46	C-E-D
5130131703001200	300 x 1200	10 (2+2)	30	255	70-90	85-105	55-75	15	159	1,75	1,75	C-E-D
5130131703001500	300 x 1500	12 (2+2)	30	255	70-90	85-105	55-75	15	166	2,19	2,19	C-E-D
5130131703001700	300 x 1700	14 (2+2)	30	255	70-90	85-105	55-75	15	154	2,48	2,48	C-E-D
5130131704000700	400 x 700	6 (2+2)	30	355	70-90	85-105	55-75	15	172	1,03	1,03	C-E-D
5130131704001000	400 x 1000	8 (2+2)	30	355	70-90	85-105	55-75	15	180	1,46	1,46	C-E-D
5130131704001200	400 x 1200	10 (2+2)	30	355	70-90	85-105	55-75	15	159	1,75	1,75	C-E-D
5130131704001500	400 x 1500	12 (2+2)	30	355	70-90	85-105	55-75	15	166	2,19	2,19	C-E-D
5130131704001700	400 x 1700	14 (2+2)	30	355	70-90	85-105	55-75	15	154	2,48	2,48	C-E-D
5130131705000700	500 x 700	6 (2+2)	30	455	70-90	85-105	55-75	15	172	1,03	1,03	C-E-D
5130131705001000	500 x 1000	8 (2+2)	30	455	70-90	85-105	55-75	15	180	1,46	1,46	C-E-D
5130131705001200	500 x 1200	10 (2+2)	30	455	70-90	85-105	55-75	15	159	1,75	1,75	C-E-D
5130131705001500	500 x 1500	12 (2+2)	30	455	70-90	85-105	55-75	15	166	2,19	2,19	C-E-D
5130131705001700	500 x 1700	14 (2+2)	30	455	70-90	85-105	55-75	15	154	2,48	2,48	C-E-D
5130131706000700	600 x 700	6 (2+2)	30	555	70-90	85-105	55-75	15	172	1,03	1,03	C-E-D
5130131706001000	600 x 1000	8 (2+2)	30	555	70-90	85-105	55-75	15	180	1,46	1,46	C-E-D
5130131706001200	600 x 1200	10 (2+2)	30	555	70-90	85-105	55-75	15	159	1,75	1,75	C-E-D
5130131706001500	600 x 1500	12 (2+2)	30	555	70-90	85-105	55-75	15	166	2,19	2,19	C-E-D
5130131706001700	600 x 1700	14 (2+2)	30	555	70-90	85-105	55-75	15	154	2,48	2,48	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5130131703000700	153	522	199	679
5130131703001000	210	717	273	931
5130131703001200	257	877	335	1143
5130131703001500	314	1071	409	1395
5130131703001700	362	1235	471	1607
5130131704000700	194	662	253	863
5130131704001000	264	901	344	1174
5130131704001200	326	1112	424	1446
5130131704001500	396	1351	515	1757
5130131704001700	457	1559	595	2029
5130131705000700	236	805	307	1047
5130131705001000	321	1095	418	1426
5130131705001200	397	1354	517	1763
5130131705001500	481	1641	626	2135
5130131705001700	557	1900	725	2473
5130131706000700	281	959	366	1249
5130131706001000	380	1296	494	1685
5130131706001200	471	1607	613	2091
5130131706001500	570	1944	741	2527
5130131706001700	661	2255	860	2933

LOGISTICS INFORMATION

MODEL CODE	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
5130131703000700	1,6	2,2	0,02	800 x 340 x 55
5130131703001000	2	2,8	0,03	1100 x 340 x 55
5130131703001200	2,4	3,3	0,03	1300 x 340 x 55
5130131703001500	2,8	4,3	0,03	1600 x 340 x 55
5130131703001700	3,2	4,8	0,04	1800 x 340 x 55
5130131704000700	1,8	2,5	0,02	800 x 440 x 55
5130131704001000	2,3	3,3	0,03	1100 x 440 x 55
5130131704001200	2,8	3,9	0,04	1300 x 440 x 55
5130131704001500	3,3	5,1	0,06	1600 x 440 x 85
5130131704001700	3,8	5,7	0,07	1800 x 440 x 85
5130131705000700	2	3	0,04	800 x 540 x 85
5130131705001000	2,6	3,9	0,06	1100 x 540 x 85
5130131705001200	3,2	4,6	0,06	1300 x 540 x 85
5130131705001500	3,8	4,7	0,05	1600 x 540 x 55
5130131705001700	4,3	5,4	0,06	1800 x 540 x 55
5130131706000700	2,3	2,8	0,03	800 x 640 x 55
5130131706001000	3	3,6	0,04	1100 x 640 x 55
5130131706001200	3,6	4,3	0,05	1300 x 640 x 55
5130131706001500	4,3	5,4	0,06	1600 x 640 x 55
5130131706001700	4,9	6,2	0,07	1800 x 640 x 55