

MONA

TECHNICAL INFORMATION											(For connection types, please refer to the last page)
MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050101806340765	634X765	3	45	604	35-44	63-72	22-31	15	200	0,98	C-E-D
5050101806340965	634X965	3	45	604	35-44	63-72	22-31	15	200	1,15	C-E-D
5050101806741465	674X1465	3	45	644	35-44	63-72	22-31	15	200	1,61	C-E-D

HEAT OUTPUTS INFORMATION				
MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050101806340765	328	1 119	427	1457
5050101806340965	422	1440	549	1873
5050101806741465	231	788	301	1027

LOGISTICS INFORMATION			
Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
6.91	8.96	0,06	681X890X87
8.53	10.90	0,07	681X1090X87
12.72	16.01	0,10	721X1590X87

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel