

PENORA

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050102005651465	565X1465	7	84	535	69.5	111,5	27.5	15	40	2,20	C-E-D
5050102007290765	729X765	11	84	699	69.5	111,5	27.5	15	40	1,59	C-E-D
5050102006270965	627X965	9	84	597	69.5	111,5	27.5	15	40	1,73	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050102005651465	225	768	293	1000
5050102007290765	702	2394	913	3114
5050102006270965	787	2684	1024	3492

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
16.36	19.41	0,13	612X1590X126
11.87	14.18	0,09	776X890X126
12.94	15.36	0,10	674X1090X126

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel