

THAMES		TECHNICAL INFORMATION (For connection types, please refer to the last page)									
MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050102605960965	596X965	6	44	566	37-46	63-72	26-35	15	70	1,41	C-E-D
5050102607440765	744X765	8	44	714	37-46	63-72	26-35	15	70	1,40	C-E-D
5050102605621465	562X1465	5	44	532	37-46	63-72	26-35	15	70	1,86	C-E-D

HEAT OUTPUTS INFORMATION				
MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050102605960965	462	1576	601	2050
5050102607440765	450	1535	585	1995
5050102605621465	225	768	293	1000

LOGISTICS INFORMATION			
Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.87	10.11	0,07	643X1090X86
7.84	10.05	0,07	791X890X86
10.22	13.11	0,09	609X1590X86

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel