

**VOGUE DOUBLE PLUS**

**TECHNICAL INFORMATION**

(For connection types, please refer to the last page)

MODEL CODE	Width x Height ( W x H )	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030105205001200	500X1200	10	56	455	56,5	84,5	28,5	15	30	1,55	C-E-D
5030105205001400	500X1400	14	56	455	56,5	84,5	28,5	15	30	1,66	C-E-D
5030105205001600	500X1600	18	56	455	56,5	84,5	28,5	15	30	1,77	C-E-D
<b>5030105205001800</b>	500X1800	22	56	455	56,5	84,5	28,5	15	30	1,89	C-E-D


**HEAT OUTPUTS INFORMATION**

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030105205001200	559	1907	727	2480
5030105205001400	583	1989	758	2585
5030105205001600	610	2081	793	2705
5030105205001800	641	2186	834	2844

**LOGISTICS INFORMATION**

Net Weight	Gross Weight	Package Volume	Package Dimensions ( W x H x D )
kg	kg	m³	mm
11.83	14.05	0,07	532X1330X98
12.48	14.97	0,08	532X1530X98
13.13	15.89	0,10	532X1730X98
13.79	16.94	0,11	532X1930X98

**CONNECTIONS TYPE**



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

**C: Central Heating / E: Electric / D: Dual Fuel**