

TECHNICAL INFORMATION

Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Space Between Groups (G)	Tube Width (F)	Water Volume	Fuel Type	Prices Ex. Vat
mm	pieces	mm	mm	mm	mm	mm	mm	mm	mm	L		
300 x 570	3 (1+1)	40	255	47/56	74/83	34/43	170		70	0,33	C-E-D	£ 57.00
300 x 810	4 (1+1)	40	255	47/56	74/83	34/43	170		70	0,46	C-E-D	£ 77.00
300 x 1050	5 (1+1)	40	255	47/56	74/83	34/43	170		70	0,60	C-E-D	£ 99.00
300 x 1290	6 (1+1)	40	255	47/56	74/83	34/43	170		70	0,74	C-E-D	£ 118.00
300 x 1530	7 (1+1)	40	255	47/56	74/83	34/43	170		70	0,87	C-E-D	£ 142.00
300 x 1770	8 (1+1)	40	255	47/56	74/83	34/43	170		70	1,01	C-E-D	£ 164.00
400 x 570	3 (1+1)	40	355	47/56	74/83	34/43	170		70	0,33	C-E-D	£ 60.00
400 x 810	4 (1+1)	40	355	47/56	74/83	34/43	170		70	0,46	C-E-D	£ 81.00
400 x 1050	5 (1+1)	40	355	47/56	74/83	34/43	170		70	0,60	C-E-D	£ 104.00
400 x 1290	6 (1+1)	40	355	47/56	74/83	34/43	170		70	0,74	C-E-D	£ 124.00
400 x 1530	7 (1+1)	40	355	47/56	74/83	34/43	170		70	0,87	C-E-D	£ 149.00
400 x 1770	8 (1+1)	40	355	47/56	74/83	34/43	170		70	1,01	C-E-D	£ 173.00
500 x 570	3 (1+1)	40	455	47/56	74/83	34/43	170		70	0,33	C-E-D	£ 63.00
500 x 810	4 (1+1)	40	455	47/56	74/83	34/43	170		70	0,46	C-E-D	£ 85.00
500 x 1050	5 (1+1)	40	455	47/56	74/83	34/43	170		70	0,60	C-E-D	£ 109.00
500 x 1290	6 (1+1)	40	455	47/56	74/83	34/43	170		70	0,74	C-E-D	£ 130.00
500 x 1530	7 (1+1)	40	455	47/56	74/83	34/43	170		70	0,87	C-E-D	£ 156.00
500 x 1770	8 (1+1)	40	455	47/56	74/83	34/43	170		70	1,01	C-E-D	£ 181.00
600 x 570	3 (1+1)	40	555	47/56	74/83	34/43	170		70	0,33	C-E-D	£ 66.00
600 x 810	4 (1+1)	40	555	47/56	74/83	34/43	170		70	0,46	C-E-D	£ 89.00
600 x 1050	5 (1+1)	40	555	47/56	74/83	34/43	170		70	0,60	C-E-D	£ 114.00
600 x 1290	6 (1+1)	40	555	47/56	74/83	34/43	170		70	0,74	C-E-D	£ 136.00
600 x 1530	7 (1+1)	40	555	47/56	74/83	34/43	170		70	0,87	C-E-D	£ 163.00
600 x 1770	8 (1+1)	40	555	47/56	74/83	34/43	170		70	1,01	C-E-D	£ 189.00

HEAT OUTPUTS INFORMATION

Width x Height (W x H)	Heat Outputs	ΔT 50 °C	Heat Outputs ΔT 60 °C	
		Btu	Watt	Btu
mm	Watt	Btu	Watt	Btu
300 x 570	126	430	164	560
300 x 810	175	597	228	778
300 x 1050	225	768	293	1000
300 x 1290	274	935	357	1218
300 x 1530	323	1102	420	1433
300 x 1770	372	1269	484	1651
400 x 570	153	522	199	679
400 x 810	211	720	275	938
400 x 1050	269	918	350	1194
400 x 1290	327	1116	426	1453
400 x 1530	385	1313	501	1709
400 x 1770	443	1511	576	1965
500 x 570	180	614	234	798
500 x 810	248	846	323	1102
500 x 1050	315	1075	410	1399
500 x 1290	382	1303	497	1695
500 x 1530	449	1532	584	1992
500 x 1770	517	1763	673	2295
600 x 570	209	713	272	928
600 x 810	286	976	372	1269
600 x 1050	363	1238	472	1610
600 x 1290	440	1501	572	1951
600 x 1530	517	1763	673	2295
600 x 1770	593	2023	771	2630

LOGISTICS INFORMATION

Width x Height (W x H)	Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
mm	kg	kg	m³	mm
300 x 570	2,7	3,1	0,02	670 x 340 x 60
300 x 810	3,6	4,2	0,02	910 x 340 x 60
300 x 1050	4,6	5,2	0,03	1150 x 340 x 60
300 x 1290	5,5	6,3	0,03	1390 x 340 x 60
300 x 1530	6,4	7,4	0,04	1630 x 340 x 60
300 x 1770	7,3	8,4	0,04	1870 x 340 x 60
400 x 570	3	3,5	0,02	670 x 440 x 55
400 x 810	4	4,7	0,03	910 x 440 x 55
400 x 1050	5	5,9	0,03	1150 x 440 x 55
400 x 1290	6	7	0,04	1390 x 440 x 55
400 x 1530	7	8,2	0,04	1630 x 440 x 55
400 x 1770	8	9,4	0,05	1870 x 440 x 55
500 x 570	3,2	3,9	0,02	670 x 540 x 55
500 x 810	4,3	5,2	0,03	910 x 540 x 55
500 x 1050	5,4	6,5	0,04	1150 x 540 x 55
500 x 1290	6,5	7,8	0,05	1390 x 540 x 55
500 x 1530	7,6	9,1	0,05	1630 x 540 x 55
500 x 1770	8,7	10,4	0,06	1870 x 540 x 55
600 x 570	3,5	4,2	0,03	670 x 640 x 55
600 x 810	4,7	5,7	0,04	910 x 640 x 55
600 x 1050	5,9	7,1	0,05	1150 x 640 x 55
600 x 1290	7,1	8,5	0,05	1390 x 640 x 55
600 x 1530	8,3	10	0,06	1630 x 640 x 55
600 x 1770	9,5	11,4	0,07	1870 x 640 x 55

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3	TR
x	x	x	x	x	x	⇒ ✓